	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A120	18		No	events found						
AWNG_A121	22		0.00	153.33	100.00	1,342.50	65.22%	60.61%	39.8%	25.95%
AWNG_A122	22		0.00	153.33	0.92	19.25	0.6%	95.45%	0.57%	0%
AWNG_A123	20		0.00	153.33	101.25	1,502.50	66.03%	76.25%	48.99%	32.35%
AWNG_A124	20		0.00	153.33	113.75	2,105.00	74.18%	93.33%	68.64%	50.92%
AWNG_A125	22		0.00	153.33	90.33	1,394.00	58.91%	75.76%	41.32%	24.35%
AWNG_A135	28		No	events found						
JWNG_J130	20		0.00	153.33	13.42	104.67	8.75%	40.56%	3.41%	0.3%
KWNG_K104	21		0.00	153.33	38.58	534.25	25.16%	82.74%	16.59%	4.17%
KWNG_K105	18		0.00	153.33	27.50	440.00	17.93%	88.89%	15.94%	2.86%
KWNG_K107	19		0.00	153.33	42.50	681.25	27.72%	81.58%	23.38%	6.48%
KWNG_K109	23		0.00	153.33	42.92	514.33	27.99%	69.17%	14.58%	4.08%
KWNG_K110	16		0.00	153.33	12.33	235.83	8.04%	84.38%	9.61%	0.77%
KWNG_K111	24		0.00	153.33	115.00	2,558.75	75%	93.06%	69.53%	52.15%
KWNG_K114	20		0.00	153.33	29.67	392.08	19.35%	82.5%	12.79%	2.47%
LWNG_L105	21		0.00	153.33	76.67	607.58	50%	12.86%	18.87%	9.43%
MWNG_M100	20		0.00	153.33	31.17	502.58	20.33%	73.57%	16.39%	3.33%
MWNG_M103	20		0.00	153.33	18.00	230.50	11.74%	65%	7.52%	0.88%
SWNG_S101	21		0.00	153.33	115.00	1,725.00	75%	71.43%	53.57%	40.18%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A035	24		7.67	145.67	28.75	264.33	19.74%	54.69%	7.56%	1.49%
AWNG_A203	30		0.00	153.33	72.50	997.50	47.28%	46.67%	21.68%	10.25%
AWNG_A204	30		0.00	153.33	70.00	1,582.50	45.65%	55%	34.4%	15.71%
AWNG_A205	36		0.00	153.33	41.25	781.25	26.9%	59.72%	14.15%	3.81%
AWNG_A206	30		0.00	153.33	70.00	1,680.00	45.65%	80%	36.52%	16.67%
AWNG_A207	36		0.00	153.33	85.00	2,077.50	55.43%	62.5%	37.64%	20.86%
AWNG_A208	30		0.00	153.33	85.00	2,207.50	55.43%	88.33%	47.99%	26.6%
AWNG_A209	36		0.00	153.33	70.00	945.00	45.65%	50%	17.12%	7.82%
AWNG_A211	24		0.00	153.33	115.00	2,012.50	75%	72.92%	54.69%	41.02%
AWNG_A213	30		0.00	153.33	69.50	1,400.00	45.33%	64.44%	30.43%	13.79%
CWNG_C111	58		0.00	153.33	140.83	13,473.25	91.85%	34.73%	151.5%	139.15%
DWNG_D133	40		0.00	153.33	101.58	2,248.25	66.25%	54.17%	36.66%	24.28%
DWNG_D135	40		0.00	153.33	1.92	76.67	1.25%	100%	1.25%	0.02%
EWNG_E110	38		0.00	153.33	63.58	1,575.83	41.47%	64.47%	27.05%	11.21%
EWNG_E112	38		0.00	153.33	31.92	816.42	20.82%	76.84%	14.01%	2.92%
EWNG_E114	32		0.00	153.33	42.50	876.25	27.72%	67.19%	17.86%	4.95%
EWNG_E116	32		0.00	153.33	103.92	1,628.42	67.77%	42.71%	33.19%	22.49%
FWNG_F012	32		0.00	153.33	36.25	599.00	23.64%	35%	12.21%	2.89%
FWNG_F020	24		0.00	153.33	46.00	770.67	30%	71.67%	20.94%	6.28%
FWNG_F023	32		0.00	153.33	59.25	2,008.75	38.64%	209.38%	40.94%	15.82%
FWNG_F024	32		0.00	153.33	52.67	1,805.83	34.35%	153.65%	36.8%	12.64%
FWNG_F025	50		0.00	153.33	30.58	1,413.67	19.95%	77%	18.44%	3.68%
FWNG_F026	32		0.00	153.33	49.83	1,274.67	32.5%	99.84%	25.98%	8.44%
FWNG_F027	32		0.00	153.33	28.00	1,140.00	18.26%	131.25%	23.23%	4.24%
FWNG_F028	32		0.00	153.33	38.17	1,029.83	24.89%	133.81%	20.99%	5.22%
FWNG_F029	32		0.00	153.33	24.17	469.25	15.76%	64.49%	9.56%	1.51%
FWNG_F031	32		0.00	153.33	22.17	532.00	14.46%	75%	10.84%	1.57%
FWNG_F032	32		0.00	153.33	23.00	668.92	15%	91.19%	13.63%	2.04%
FWNG_F033	32		0.00	153.33	20.42	496.92	13.32%	85.11%	10.13%	1.35%
FWNG_F034	32		0.00	153.33	33.92	498.42	22.12%	45.88%	10.16%	2.25%

	(A) Max	(B) Fill	(C) Blackout	(D) Possible	(E) Hours	(F) Contact	(G) Time	(H) Class Seat	(I) Station	(J) Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F035	24		0.00	153.33	36.67	588.33	23.91%	52.08%	15.99%	3.82%
FWNG_F036	30		0.00	153.33	13.75	343.75	8.97%	83.33%	7.47%	0.67%
FWNG_F120	32		0.00	153.33	69.67	1,268.83	45.43%	57.59%	25.86%	11.75%
FWNG_F130	24		0.00	153.33	42.42	748.58	27.66%	77.08%	20.34%	5.63%
FWNG_F264	32		0.00	153.33	22.83	475.50	14.89%	72.57%	9.69%	1.44%
FWNG_F282	20		0.00	153.33	115.00	1,725.00	75%	75%	56.25%	42.19%
GWNG_G163	25		No	events found						
JWNG_J132	32		No	events found						
JWNG_J133	32		0.00	153.33	100.00	2,151.25	65.22%	58.33%	43.84%	28.59%
JWNG_J134	32		0.00	153.33	100.00	2,097.50	65.22%	63.54%	42.75%	27.88%
JWNG_J135	32		0.00	153.33	14.42	338.33	9.4%	68.75%	6.9%	0.65%
JWNG_J136	32		0.00	153.33	55.00	1,332.50	35.87%	76.56%	27.16%	9.74%
JWNG_J137	32		0.00	153.33	115.00	2,660.00	75%	66.67%	54.21%	40.66%
JWNG_J138	32		0.00	153.33	41.25	632.50	26.9%	51.56%	12.89%	3.47%
JWNG_J139	32		0.00	153.33	42.50	1,062.50	27.72%	78.12%	21.65%	6%
JWNG_J140	32		0.00	153.33	55.00	1,347.50	35.87%	76.56%	27.46%	9.85%
JWNG_J141	32		0.00	153.33	12.50	287.50	8.15%	71.88%	5.86%	0.48%
KWNG_K116	26		0.00	153.33	28.75	603.75	18.75%	80.77%	15.14%	2.84%
LWNG_L112	24		0.00	153.33	89.42	1,849.25	58.32%	68.75%	50.25%	29.3%
LWNG_L114	24		0.00	153.33	128.75	2,802.50	83.97%	91.67%	76.15%	63.95%
LWNG_L131	34		0.00	153.33	90.08	816.50	58.75%	27.21%	15.66%	9.2%
LWNG_L141	20		0.00	153.33	76.50	465.00	49.89%	37.5%	15.16%	7.57%
MWNG_M104	30		0.00	153.33	83.75	2,217.50	54.62%	91.11%	48.21%	26.33%
MWNG_M105	24		0.00	153.33	143.75	7,513.33	93.75%	105.56%	204.17%	191.41%
MWNG_M151	30		0.00	153.33	22.25	282.92	14.51%	53.33%	6.15%	0.89%
MWNG_M163	30		0.00	153.33	35.25	574.83	22.99%	50.83%	12.5%	2.87%
NWNG_N202	28		0.00	153.33	13.75	330.00	8.97%	85.71%	7.69%	0.69%
NWNG_N210	30		No	events found						
PWNG_P110	28		0.00	153.33	56.25	1,068.75	36.68%	67.86%	24.89%	9.13%
SWNG_S034	25		0.00	153.33	72.50	1,232.50	47.28%	68%	32.15%	15.2%
SWNG_S035	25		0.00	153.33	59.08	1,089.08	38.53%	48%	28.41%	10.95%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S036	25		0.00	153.33	116.92	1,956.92	76.25%	55%	51.05%	38.93%
SWNG_S037	25		0.00	153.33	72.83	1,426.58	47.5%	61%	37.22%	17.68%
SWNG_S038	25		No	o events found						
SWNG_S039	25		0.00	153.33	0.92	18.33	0.6%	80%	0.48%	0%
SWNG_S040	25		0.00	153.33	27.92	503.33	18.21%	76%	13.13%	2.39%
SWNG_S054	25		0.00	153.33	55.00	962.50	35.87%	70.67%	25.11%	9.01%
SWNG_S055	30		0.00	153.33	85.00	1,462.50	55.43%	53.33%	31.79%	17.62%
SWNG_S056	28		0.00	153.33	40.33	806.67	26.3%	71.43%	18.79%	4.94%
SWNG_S057	28		0.00	153.33	27.50	192.50	17.93%	25%	4.48%	0.8%
SWNG_S058	30		0.00	153.33	12.50	225.00	8.15%	60%	4.89%	0.4%
SWNG_S059	28		0.00	153.33	100.00	1,627.50	65.22%	57.14%	37.91%	24.72%
SWNG_S060	24		No	o events found						
SWNG_S105	77		0.00	153.33	36.33	2,352.92	23.7%	66.02%	19.93%	4.72%
SWNG_S111	30		0.00	153.33	86.92	1,620.00	56.68%	66.67%	35.22%	19.96%
SWNG_S113	30		0.00	153.33	26.25	525.00	17.12%	66.67%	11.41%	1.95%
SWNG_S125	60		0.00	153.33	56.92	1,407.50	37.12%	43.33%	15.3%	5.68%
SWNG_S220	25		0.00	153.33	63.92	1,597.92	41.68%	100%	41.68%	17.38%
SWNG_S221	28		0.00	153.33	83.75	1,530.00	54.62%	66.67%	35.64%	19.46%
SWNG_S224	28		0.00	153.33	12.50	125.00	8.15%	35.71%	2.91%	0.24%
SWNG_S225	28		0.00	153.33	27.50	412.50	17.93%	53.57%	9.61%	1.72%
SWNG_S226	28		0.00	153.33	27.50	687.50	17.93%	89.29%	16.01%	2.87%
SWNG_S228	28		No	o events found						
SWNG_S253	30		0.00	153.33	57.50	1,210.00	37.5%	61.67%	26.3%	9.86%
SWNG_S258	25		0.00	153.33	41.25	825.00	26.9%	80%	21.52%	5.79%
SWNG_S260	28		0.00	153.33	70.00	1,202.50	45.65%	62.5%	28.01%	12.79%
SWNG_S261	20		0.00	153.33	71.92	1,181.33	46.9%	65%	38.52%	18.07%
SWNG_S263	30		0.00	153.33	70.00	800.00	45.65%	24.44%	17.39%	7.94%
SWNG_S264	24		0.00	153.33	71.67	1,430.42	46.74%	76.04%	38.87%	18.17%
SWNG_S266	28		0.00	153.33	42.50	297.50	27.72%	25%	6.93%	1.92%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Max CapacityFill RatioBlackout HousPosci HousContact HousContact HousContact HousContact HousContact HousContact HousContact HousContact HousContact HousVisitazionWitizztionWitiztionWitiztion		(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
CWNG_C110     25     0.00     153.33     1.42     566.67     0.92%     1600%     14.78%     0.14%       CWNG_C113     25     0.00     153.33     115.00     2.242.50     75%     78%     68.5%     43.8%       CWNG_C114     25     0.00     153.33     1.42     566.67     0.92%     1600%     14.78%     0.14%       CWNG_C117     25     0.00     153.33     1.42     566.67     0.92%     1600%     14.78%     0.14%       CWNG_C119     20     0.00     153.33     112.00     2.300.00     75%     60%     45%       CWNG_C123     25     0.00     153.33     112.07     2.400.00     83.97%     96.67%     80.22%     67.36%       CWNG_C132     20     0.00     153.33     128.75     2.400.00     83.97%     96.67%     80.22%     67.36%       CWNG_C134     24     0.00     153.33     85.00     1.652.50     55.43%     80.26%     3.75%     9.2%     3.45%     12.9%		Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
CWNG_C113     25     0.00     153.33     115.00     2.242.50     75%     78%     58.5%     43.88%       CWNG_C114     25     0.00     153.33     112.00     150.00     17.33%     80%     14.35%     2.57%       CWNG_C116     25     0.00     153.33     115.00     2.300.00     75%     80%     60%     4.45%       CWNG_C117     25     0.00     153.33     115.00     2.300.00     75%     80%     60%     65.8%       CWNG_C123     25     0.00     153.33     115.00     2.400.00     83.97%     90.67%     80.22%     67.3%       CWNG_C132     20     0.00     153.33     75.0     1.325.0     35.5%     80.67%     80.22%     67.3%       CWNG_C132     20     0.00     153.33     75.0     1.325.0     35.5%     92%     34.5%     12.9%       CWNG_E131     30     No events found      75.5%     14.375     14.375     80.5%     44.9%     24.8%       EWNG_E11		Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
CWNG_C114     25     0.00     153.33     27.50     550.00     17.93%     80%     14.35%     2.57%       CWNG_C116     25     0.00     153.33     1142     666.67     0.2%     100%     14.78%     0.14%       CWNG_C117     25     0.00     153.33     115.00     2.302.00     75%     80%     669.85%       CWNG_C123     25     0.00     153.33     115.00     2.392.50     75%     110.67%     75.5%     57.38%       CWNG_C131     20     No events found	CWNG_C110	25		0.00	153.33	1.42	566.67	0.92%	1600%	14.78%	0.14%
CWNG_C116     25     0.00     153.33     1.42     566.67     0.92%     1600%     14.78%     0.14%       CWNG_C117     25     0.00     153.33     115.00     2.300.00     75%     80%     66%     45%       CWNG_C113     20     0.00     153.33     115.00     2.300.00     75%     80%     76.5%     57.3%       CWNG_C123     25     0.00     153.33     115.00     2.400.00     83.97%     90%     78.42%     65.65%       CWNG_C131     20     No events found     75.5     2.400.00     83.97%     90%     78.5%     67.3%       CWNG_C132     20     0.00     153.33     128.75     1.322.50     75.5%     82.6%     12.9%       CWNG_C138     25     0.00     153.33     85.00     155.25     55.43%     80.56%     44.9%     24.89%       EWNG_E117     25     0.00     153.33     86.25     120.750     56.25%     56.9%     31.5%     17.2%       EWNG_E118     25 <t< td=""><td>CWNG_C113</td><td>25</td><td></td><td>0.00</td><td>153.33</td><td>115.00</td><td>2,242.50</td><td>75%</td><td>78%</td><td>58.5%</td><td>43.88%</td></t<>	CWNG_C113	25		0.00	153.33	115.00	2,242.50	75%	78%	58.5%	43.88%
CWNG_C117     25     0.00     153.33     115.00     2.300.00     75%     80%     60%     44%       CWNG_C119     20     0.00     153.33     128.75     2.405.00     83.97%     90%     78.42%     66.86%       CWNG_C123     25     0.00     153.33     115.00     2.932.50     75%     110.67%     76.42%     65.86%       CWNG_C131     20     No events found      2.932.50     75%     96.67%     80.22%     67.96%       CWNG_C136     24     No events found      77.5%     96.67%     80.22%     67.96%       CWNG_C136     24     No events found      77.5%     96.67%     80.22%     67.96%       EWNG_E111     30     No events found      77.5%     92.67%     80.22%     67.96%     24.89%       EWNG_E117     25     0.00     153.33     85.00     1.852.50     55.43%     80.66%     44.9%     24.89%       EWNG_E117     25     0.00     153.33     82.70 <t< td=""><td>CWNG_C114</td><td>25</td><td></td><td>0.00</td><td>153.33</td><td>27.50</td><td>550.00</td><td>17.93%</td><td>80%</td><td>14.35%</td><td>2.57%</td></t<>	CWNG_C114	25		0.00	153.33	27.50	550.00	17.93%	80%	14.35%	2.57%
CWNG_C119     20     0.00     153.33     128.75     2.405.00     83.97%     90%     78.42%     65.85%       CWNG_C123     25     0.00     153.33     115.00     2.92.50     75%     110.67%     765.5%     57.38%       CWNG_C131     20     No events found	CWNG_C116	25		0.00	153.33	1.42	566.67	0.92%	1600%	14.78%	0.14%
CWNG_C123     25     0.00     153.33     115.00     2,932.50     75%     110.67%     76.5%     57.38%       CWNG_C131     20     No events found     2     260.00     153.33     22.60.00     8.97%     96.67%     80.22%     67.38%       CWNG_C132     20     0.00     153.33     75.50     1,322.50     37.5%     92%     34.5%     12.94%       CWNG_C138     25     0.00     153.33     85.00     1,652.50     55.43%     80.56%     44.9%     24.85%       EWNG_E111     30     No events found      55.43%     80.56%     44.9%     24.85%       EWNG_E117     25     0.00     153.33     86.25     1.207.50     56.25%     56%     31.5%     17.7%       EWNG_E118     25     0.00     153.33     86.25     1.207.50     56.25%     56%     8.97%     1.61%       EWNG_E137     24     0.00     153.33     86.58     2.002.25     56.47%     96.83%     59.44%     30.74%	CWNG_C117	25		0.00	153.33	115.00	2,300.00	75%	80%	60%	45%
CWNQ_C131     20     No events found       CWNQ_C132     20     0.00     f53.33     128.75     2.460.00     83.97%     96.67%     80.22%     67.36%       CWNQ_C133     24     No events found          7.36%     2.460.00     1,322.50     37.5%     92%     34.5%     12.94%     2.460.00     153.33     57.50     1,322.50     35.5%     92%     34.5%     12.94%     2.48%	CWNG_C119	20		0.00	153.33	128.75	2,405.00	83.97%	90%	78.42%	65.85%
CWNG_C132     20     0.00     153.33     128.75     2,460.00     83.97%     96.87%     80.22%     67.38%       CWNG_C138     25     0.00     153.33     57.50     1.322.50     37.5%     92%     34.5%     12.94%       EWNG_C138     25     0.00     153.33     85.00     1.552.50     55.43%     80.56%     44.9%     24.89%       EWNG_E113     24     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     0.7%       EWNG_E118     25     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     17.72%       EWNG_E119     20     0.00     153.33     28.65     1.207.50     56.25%     56.9%     31.5%     17.72%       EWNG_E131     24     0.00     153.33     86.25     1.207.50     56.25%     26.83%     5.99%     1.72%       EWNG_E131     24     0.00     153.33     86.55     2.003.25     56.47%     95.83%     54.44%     30.74%     8.940% <td>CWNG_C123</td> <td>25</td> <td></td> <td>0.00</td> <td>153.33</td> <td>115.00</td> <td>2,932.50</td> <td>75%</td> <td>110.67%</td> <td>76.5%</td> <td>57.38%</td>	CWNG_C123	25		0.00	153.33	115.00	2,932.50	75%	110.67%	76.5%	57.38%
CWNG_C136     24     No events found       CWNG_C138     25     0.00     153.33     57.50     1,32.50     37.5%     92%     34.5%     12.94%       EWNG_E111     30     No events found       55.43%     80.56%     44.9%     24.89%       EWNG_E117     25     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     0.7%       EWNG_E118     25     0.00     153.33     26.75     143.75     18.75%     20%     8.97%     1.72%       EWNG_E118     25     0.00     153.33     27.50     440.00     17.93%     50%     8.97%     1.72%       EWNG_E126     24     No events found     1.294     3.00     153.33     44.08     22.042     28.75%     20.83%     5.99%     1.72%       EWNG_E131     24     0.00     153.33     86.58     2.003.25     56.47%     95.83%     5.99%     1.72%       FWNG_F005     20     0.00     153.33     63.58     627.67	CWNG_C131	20		No	events found						
CWNG_C138     25     0.00     153.33     57.50     1,322.50     37.5%     92%     34.5%     12.94%       EWNG_E111     30     No events found <td< td=""><td>CWNG_C132</td><td>20</td><td></td><td>0.00</td><td>153.33</td><td>128.75</td><td>2,460.00</td><td>83.97%</td><td>96.67%</td><td>80.22%</td><td>67.36%</td></td<>	CWNG_C132	20		0.00	153.33	128.75	2,460.00	83.97%	96.67%	80.22%	67.36%
EWNG_E111     30     No events found       EWNG_E113     24     0.00     153.33     86.00     1.652.50     55.43%     80.66%     44.9%     24.89%       EWNG_E117     25     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     0.7%       EWNG_E118     25     0.00     153.33     28.75     143.75     18.75%     20%     3.15%     17.72%       EWNG_E119     32     0.00     153.33     86.25     1.207.50     56.25%     56.9%     31.5%     17.72%       EWNG_E113     24     0.00     153.33     86.58     220.42     28.75%     20.83%     5.99%     1.172%       EWNG_E137     24     0.00     153.33     86.58     220.42     28.75%     20.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.58     20.03.25     56.47%     95.83%     54.44%     30.74%       FWNG_F008     2     0.00     153.33     63.58     627.67     41.47% </td <td>CWNG_C136</td> <td>24</td> <td></td> <td>No</td> <td>o events found</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	CWNG_C136	24		No	o events found						
EWNG_E113     24     0.00     153.33     85.00     1.652.50     55.43%     80.56%     44.9%     24.89%       EWNG_E117     25     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     0.7%       EWNG_E118     25     0.00     153.33     28.65     143.75     18.75%     20%     3.75%     0.7%       EWNG_E119     32     0.00     153.33     27.50     440.00     17.93%     50%     8.97%     1.61%       EWNG_E126     24     No events found      7.90     440.00     17.93%     50%     8.97%     1.61%       EWNG_E131     24     0.00     153.33     4.08     2.00.2     5.64.7%     95.83%     54.44%     0.74%       FWNG_E105     20     0.00     153.33     86.25     431.25     56.25%     26%     144.06%     7.91%       FWNG_F005     20     0.00     153.33     86.25     431.25     56.25%     26%     144.06%     7.91%       FWNG_F0	CWNG_C138	25		0.00	153.33	57.50	1,322.50	37.5%	92%	34.5%	12.94%
EWNG_E117     25     0.00     153.33     28.75     143.75     18.75%     20%     3.75%     0.7%       EWNG_E118     25     0.00     153.33     86.25     1.207.50     566.25%     56%     31.5%     17.72%       EWNG_E119     32     0.00     153.33     27.50     440.00     17.93%     50%     8.97%     1.61%       EWNG_E126     24     No events found      7.72%     28.75%     20.83%     5.99%     1.72%       EWNG_E131     24     0.00     153.33     86.58     2.003.25     56.47%     95.83%     54.44%     30.74%       EWNG_E137     24     0.00     153.33     86.58     2.003.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.25     431.25     56.25%     25%     14.06%     7.91%       FWNG_F013     24     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F111	EWNG_E111	30		No	events found						
WNG_E118     25     0.00     153.33     86.25     1.207.50     56.25%     56%     31.5%     17.72%       EWNG_E119     32     0.00     153.33     27.50     440.00     17.93%     50%     8.97%     1.61%       EWNG_E126     24     No events found	EWNG_E113	24		0.00	153.33	85.00	1,652.50	55.43%	80.56%	44.9%	24.89%
EWNG_E119     32     0.00     153.33     27.50     440.00     17.93%     50%     8.97%     1.61%       EWNG_E126     24     No events found	EWNG_E117	25		0.00	153.33	28.75	143.75	18.75%	20%	3.75%	0.7%
L     No events found       EWNG_E126     24     No events found     28.75%     20.83%     5.99%     1.72%       EWNG_E137     24     0.00     153.33     46.08     2.003.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.58     2.003.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.58     2.003.25     56.25%     25%     14.4%     30.74%       FWNG_F016     24     No events found	EWNG_E118	25		0.00	153.33	86.25	1,207.50	56.25%	56%	31.5%	17.72%
EWNG_E131     24     0.00     153.33     44.08     220.42     28.75%     20.83%     5.99%     1.72%       EWNG_E137     24     0.00     153.33     86.58     2,003.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.25     431.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.25     431.25     56.47%     95.83%     54.44%     7.91%       FWNG_F008     24     No events found      7.07%     7.07%     7.07%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     84.9%     7.07%     7.81%     1.46%     7.81%     1.46%     7.81%     1.46%     7.81%     1.46%     7.81%     1.46%     7.81%     1.46% <td>EWNG_E119</td> <td>32</td> <td></td> <td>0.00</td> <td>153.33</td> <td>27.50</td> <td>440.00</td> <td>17.93%</td> <td>50%</td> <td>8.97%</td> <td>1.61%</td>	EWNG_E119	32		0.00	153.33	27.50	440.00	17.93%	50%	8.97%	1.61%
EWNG_E137     24     0.00     153.33     86.58     2,003.25     56.47%     95.83%     54.44%     30.74%       FWNG_F005     20     0.00     153.33     86.25     431.25     56.25%     25%     14.06%     7.91%       FWNG_F008     24     No events found      7.07%     7.07%       FWNG_F011     24     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     43.33%     20.47%     8.49%       FWNG_F113     24     0.00     153.33     63.58     627.67     41.47%     43.33%     20.47%     8.49%       FWNG_F113     24     0.00     153.33     28.75     287.50     18.75%     41.67%     7.81%     1.46%       FWNG_F134     0     No events found       7.81%     1.46%       FWNG_F141     0     No events found	EWNG_E126	24		No	events found						
FWNG_F005     20     0.00     153.33     86.25     431.25     56.25%     25%     14.06%     7.91%       FWNG_F008     24     No events found	EWNG_E131	24		0.00	153.33	44.08	220.42	28.75%	20.83%	5.99%	1.72%
FWNG_F008     24     No events found       FWNG_F011     24     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     43.33%     20.47%     8.49%       FWNG_F111     24     No events found	EWNG_E137	24		0.00	153.33	86.58	2,003.25	56.47%	95.83%	54.44%	30.74%
FWNG_F011     24     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     36.11%     17.06%     7.07%       FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     43.33%     20.47%     84.99%       FWNG_F111     24     No events found     V     V     V     84.99%       FWNG_F113     24     0.00     153.33     28.75     287.50     18.75%     41.67%     7.81%     1.46%       FWNG_F134     0     No events found     V	FWNG_F005	20		0.00	153.33	86.25	431.25	56.25%	25%	14.06%	7.91%
FWNG_F015     20     0.00     153.33     63.58     627.67     41.47%     43.33%     20.47%     84.99%       FWNG_F111     24     No events found	FWNG_F008	24		No	events found						
FWNG_F111     24     No events found       FWNG_F113     24     0.00     153.33     28.75     287.50     18.75%     41.67%     7.81%     1.46%       FWNG_F134     0     No events found         1.46%       FWNG_F134     0     No events found           1.46%       FWNG_F140     0     No events found	FWNG_F011	24		0.00	153.33	63.58	627.67	41.47%	36.11%	17.06%	7.07%
FWNG_F113     24     0.00     153.33     28.75     287.50     18.75%     41.67%     7.81%     1.46%       FWNG_F134     0     No events found <td< td=""><td>FWNG_F015</td><td>20</td><td></td><td>0.00</td><td>153.33</td><td>63.58</td><td>627.67</td><td>41.47%</td><td>43.33%</td><td>20.47%</td><td>8.49%</td></td<>	FWNG_F015	20		0.00	153.33	63.58	627.67	41.47%	43.33%	20.47%	8.49%
FWNG_F1340No events foundFWNG_F1400No events foundFWNG_F1410No events foundFWNG_F1420No events found	FWNG_F111	24		No	events found						
FWNG_F1400No events foundFWNG_F1410No events foundFWNG_F1420No events found	FWNG_F113	24		0.00	153.33	28.75	287.50	18.75%	41.67%	7.81%	1.46%
FWNG_F1410No events foundFWNG_F1420No events found	FWNG_F134	0		No	events found						
FWNG_F142 0 No events found	FWNG_F140	0		No	events found						
-	FWNG_F141	0		No	o events found						
FWNG_F143 0 No events found	FWNG_F142	0		No	events found						
	FWNG_F143	0		No	o events found						

			(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F144	0			o events found						
FWNG_F145	0		No	events found						
FWNG_F146	0		No	events found						
FWNG_F150	50		0.00	153.33	115.00	1,752.50	75%	30.5%	22.86%	17.14%
FWNG_F158	20		0.00	153.33	59.42	1,303.33	38.75%	80%	42.5%	16.47%
FWNG_F268	24		0.00	153.33	62.33	949.67	40.65%	64.17%	25.81%	10.49%
FWNG_F277	10		No	o events found						
FWNG_F279	10		No	o events found						
FWNG_F283A	0		0.00	153.33	5.50	133.83	3.59%	0%	0%	0%
FWNG_F283B	0		0.00	153.33	13.25	353.83	8.64%	0%	0%	0%
FWNG_F283C	0		0.00	153.33	14.58	366.33	9.51%	0%	0%	0%
FWNG_F283D	0		0.00	153.33	2.75	62.33	1.79%	0%	0%	0%
FWNG_F284	20		0.00	153.33	32.00	429.17	20.87%	102.22%	13.99%	2.92%
FWNG_F286	0		0.00	153.33	9.83	221.50	6.41%	0%	0%	0%
FWNG_F287	0		0.00	153.33	2.83	83.17	1.85%	0%	0%	0%
FWNG_F288	20		0.00	153.33	15.83	325.50	10.33%	96.43%	10.61%	1.1%
FWNG_F289	20		0.00	153.33	23.92	578.83	15.6%	117.37%	18.88%	2.94%
FWNG_F290	20		0.00	153.33	23.00	556.83	15%	117.22%	18.16%	2.72%
FWNG_F291	20		0.00	153.33	16.17	241.00	10.54%	106.67%	7.86%	0.83%
GWNG_G162	30	0	No	o events found						
GWNG_G164	25		No	o events found						
LWNG_L118	22		0.00	153.33	15.00	153.17	9.78%	47.73%	4.54%	0.44%
LWNG_L125	20		0.00	153.33	72.83	559.67	47.5%	18.33%	18.25%	8.67%
LWNG_L126	25		0.00	153.33	7.67	76.67	5%	40%	2%	0.1%
LWNG_L126A	25		0.00	153.33	7.67	76.67	5%	40%	2%	0.1%
LWNG_L126B	25		0.00	153.33	1.92	19.17	1.25%	40%	0.5%	0.01%
LWNG_L130	34		0.00	153.33	38.33	394.83	25%	29.41%	7.57%	1.89%
LWNG_L140	20		0.00	153.33	76.50	508.50	49.89%	37.5%	16.58%	8.27%
MWNG_M110	20		0.00	153.33	80.50	322.00	52.5%	20%	10.5%	5.51%
MWNG_M115	20		No	o events found						
 MWNG_M140	20		0.00	153.33	28.75	402.50	18.75%	70%	13.13%	2.46%

Report Date: Oct 14 2019 11:54 A.M.

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
MWNG_M145	20		0.00	153.33	28.75	258.75	18.75%	22.5%	8.44%	1.58%
MWNG_M150	24		0.00	153.33	15.67	2,957.50	10.22%	3137.5%	80.37%	8.21%
MWNG_M150A	20		No	events found						
MWNG_M150B	20		No	events found						
MWNG_M150C	20		No	events found						
MWNG_M150D	20		No	events found						
MWNG_M153	30		0.00	153.33	80.50	322.00	52.5%	13.33%	7%	3.68%
MWNG_M156	20		No	events found						
MWNG_M161	30		No	events found						
MWNG_M162	30		0.00	153.33	9.58	555.83	6.25%	300%	12.08%	0.76%
NWNG_N200	24		No	events found						
NWNG_N204	18		No	events found						
NWNG_N206	26		0.00	153.33	57.50	747.50	37.5%	50%	18.75%	7.03%
NWNG_N208	24		0.00	153.33	26.58	186.08	17.34%	29.17%	5.06%	0.88%
PWNG_P120	30		0.00	153.33	15.00	285.00	9.78%	63.33%	6.2%	0.61%
PWNG_P121	30		No	events found						
PWNG_P126	30		No	events found						
PWNG_P150	30		0.00	153.33	85.58	1,538.33	55.82%	58.33%	33.44%	18.67%
PWNG_P209	30		0.00	153.33	64.67	1,224.58	42.17%	58.33%	26.62%	11.23%
PWNG_P211	30		0.00	153.33	13.75	192.50	8.97%	46.67%	4.18%	0.38%
SIML	0		No	events found						
SWNG_S041	24		0.00	153.33	13.75	151.25	8.97%	45.83%	4.11%	0.37%
SWNG_S104	25		0.00	153.33	57.50	1,150.00	37.5%	80%	30%	11.25%
SWNG_S130	16		No	events found						
SWNG_S131	60		No	events found						
SWNG_S134	25		No	events found						
SWNG_S139	20		No	events found						
SWNG_S140	20		Nc	events found						
SWNG_S201	25		No	events found						
SWNG_S204	25		0.00	153.33	27.50	550.00	17.93%	80%	14.35%	2.57%
SWNG_S232	20		No	events found						

Report Date: Oct 14 2019 11:54 A.M.

# Location Utilization Summary

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S234	20		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A120	18		No	events found						
AWNG_A121	22		0.00	393.33	179.50	2,968.50	45.64%	86.36%	34.3%	15.66%
AWNG_A122	22		0.00	393.33	211.00	2,151.00	53.64%	59.09%	24.86%	13.33%
AWNG_A123	20		0.00	393.33	272.75	3,915.50	69.34%	73.18%	49.77%	34.51%
AWNG_A124	20		0.00	393.33	199.83	3,733.92	50.81%	100.56%	47.47%	24.11%
AWNG_A125	22		0.00	393.33	136.35	2,508.25	34.67%	73.94%	28.99%	10.05%
AWNG_A135	28		393.33	-0.00	1.08	43.33	0%	142.86%	0%	0%
JWNG_J130	20		0.00	393.33	62.50	840.33	15.89%	50.38%	10.68%	1.7%
KWNG_K104	21		0.00	393.33	181.42	2,534.17	46.12%	77.66%	30.68%	14.15%
KWNG_K105	18		0.00	393.33	160.00	2,590.00	40.68%	88.89%	36.58%	14.88%
KWNG_K107	19		0.00	393.33	193.58	2,716.25	49.22%	78.2%	36.35%	17.89%
KWNG_K109	23		0.00	393.33	155.83	2,483.92	39.62%	73.08%	27.46%	10.88%
KWNG_K110	16		0.00	393.33	148.25	2,431.25	37.69%	106.25%	38.63%	14.56%
KWNG_K111	24		0.00	393.33	209.50	4,098.00	53.26%	79.92%	43.41%	23.12%
KWNG_K114	20		0.00	393.33	200.58	2,650.67	51%	78%	33.69%	17.18%
LWNG_L105	21		0.00	393.33	220.25	1,861.42	56%	20.63%	22.54%	12.62%
MWNG_M100	20		0.00	393.33	211.08	3,117.75	53.67%	73.67%	39.63%	21.27%
MWNG_M103	20		0.00	393.33	66.08	977.33	16.8%	75.31%	12.42%	2.09%
SWNG_S101	21		0.00	393.33	268.42	5,005.83	68.24%	84.76%	60.6%	41.36%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A) Max	(B) Fill	(C) Blackout	(D) Possible	(E) Hours	(F) Contact	(G) Time	(H) Class Seat	(I) Station	(J) Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A035	24		19.67	373.67	112.50	1,308.08	30.11%	63.95%	14.59%	4.39%
AWNG_A203	30		0.00	393.33	237.50	4,582.50	60.38%	61.33%	38.83%	23.45%
AWNG_A204	30		0.00	393.33	221.25	4,297.50	56.25%	60.67%	36.42%	20.49%
AWNG_A205	36		0.00	393.33	236.25	5,343.75	60.06%	60%	37.74%	22.67%
AWNG_A206	30		0.00	393.33	222.50	5,677.50	56.57%	85.33%	48.11%	27.22%
AWNG_A207	36		0.00	393.33	252.50	4,850.00	64.19%	51.11%	34.25%	21.99%
AWNG_A208	30		0.00	393.33	222.50	4,980.00	56.57%	77.33%	42.2%	23.87%
AWNG_A209	36		0.00	393.33	175.00	3,800.00	44.49%	58.33%	26.84%	11.94%
AWNG_A211	24		0.00	393.33	267.92	5,063.33	68.11%	78.24%	53.64%	36.53%
AWNG_A213	30		0.00	393.33	222.50	5,497.50	56.57%	82%	46.59%	26.35%
CWNG_C111	58		0.00	393.33	361.92	34,595.58	92.01%	41.16%	151.65%	139.53%
DWNG_D133	40		0.00	393.33	253.50	5,990.08	64.45%	66.07%	38.07%	24.54%
DWNG_D135	40		0.00	393.33	222.17	5,288.33	56.48%	62.81%	33.61%	18.99%
EWNG_E110	38		0.00	393.33	203.42	3,975.42	51.72%	64.8%	26.6%	13.76%
EWNG_E112	38		0.00	393.33	89.17	2,268.50	22.67%	77.63%	15.18%	3.44%
EWNG_E114	32		0.00	393.33	282.50	5,942.50	71.82%	64.06%	47.21%	33.91%
EWNG_E116	32		0.00	393.33	194.25	4,100.25	49.39%	62.5%	32.58%	16.09%
FWNG_F012	32		0.00	393.33	143.58	2,138.25	36.5%	41.07%	16.99%	6.2%
FWNG_F020	24		0.00	393.33	192.00	3,337.67	48.81%	72.22%	35.36%	17.26%
FWNG_F023	32		0.00	393.33	166.67	5,982.50	42.37%	181.6%	47.53%	20.14%
FWNG_F024	32		0.00	393.33	139.67	5,130.00	35.51%	144.23%	40.76%	14.47%
FWNG_F025	50		0.00	393.33	147.75	6,586.25	37.56%	75.52%	33.49%	12.58%
FWNG_F026	32		0.00	393.33	126.67	3,756.67	32.2%	99.84%	29.85%	9.61%
FWNG_F027	32		0.00	393.33	101.58	3,858.25	25.83%	120.77%	30.65%	7.92%
FWNG_F028	32		0.00	393.33	139.83	3,785.25	35.55%	122.6%	30.07%	10.69%
FWNG_F029	32		0.00	393.33	59.58	1,180.92	15.15%	64.49%	9.38%	1.42%
FWNG_F031	32		0.00	393.33	98.75	2,370.00	25.11%	75%	18.83%	4.73%
FWNG_F032	32		0.00	393.33	105.75	3,071.58	26.89%	91.41%	24.4%	6.56%
FWNG_F033	32		0.00	393.33	87.17	2,226.00	22.16%	83.33%	17.69%	3.92%
FWNG_F034	32		0.00	393.33	111.00	1,628.58	28.22%	45.88%	12.94%	3.65%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F035	24		0.00	393.33	228.50	3,361.00	58.09%	56.25%	35.6%	20.68%
FWNG_F036	30		0.00	393.33	118.75	2,362.50	30.19%	67.5%	20.02%	6.04%
FWNG_F120	32		0.00	393.33	198.42	3,644.42	50.44%	53.12%	28.95%	14.61%
FWNG_F130	24		0.00	393.33	185.33	2,851.17	47.12%	62.88%	30.2%	14.23%
FWNG_F264	32		0.00	393.33	102.17	2,223.75	25.97%	71.56%	17.67%	4.59%
FWNG_F282	20		0.00	393.33	221.25	3,318.75	56.25%	75%	42.19%	23.73%
GWNG_G163	25		No	events found						
JWNG_J132	32		0.00	393.33	178.67	3,937.67	45.42%	74.48%	31.28%	14.21%
JWNG_J133	32		0.00	393.33	228.50	4,441.75	58.09%	60.62%	35.29%	20.5%
JWNG_J134	32		0.00	393.33	243.75	4,277.92	61.97%	53.12%	33.99%	21.06%
JWNG_J135	32		0.00	393.33	238.50	5,181.25	60.64%	66.67%	41.16%	24.96%
JWNG_J136	32		0.00	393.33	165.42	3,899.00	42.06%	72.4%	30.98%	13.03%
JWNG_J137	32		0.00	393.33	190.00	3,127.50	48.31%	50.62%	24.85%	12%
JWNG_J138	32		0.00	393.33	237.50	3,875.00	60.38%	49.55%	30.79%	18.59%
JWNG_J139	32		0.00	393.33	180.00	3,900.00	45.76%	67.71%	30.99%	14.18%
JWNG_J140	32		0.00	393.33	195.00	4,170.00	49.58%	68.12%	33.13%	16.42%
JWNG_J141	32		0.00	393.33	223.75	4,393.75	56.89%	65%	34.91%	19.86%
KWNG_K116	26		0.00	393.33	132.50	2,585.00	33.69%	75.38%	25.28%	8.51%
LWNG_L112	24		0.00	393.33	210.00	4,680.00	53.39%	94.44%	49.58%	26.47%
LWNG_L114	24		0.00	393.33	198.00	3,822.25	50.34%	67.86%	40.49%	20.38%
LWNG_L131	34		0.00	393.33	88.92	954.17	22.61%	31.18%	7.13%	1.61%
LWNG_L141	20		0.00	393.33	283.33	2,833.33	72.03%	50%	36.02%	25.94%
MWNG_M104	30		0.00	393.33	273.25	6,485.50	69.47%	81.67%	54.96%	38.18%
MWNG_M105	24		0.00	393.33	368.75	19,273.33	93.75%	105.56%	204.17%	191.41%
MWNG_M151	30		0.00	393.33	88.00	1,633.67	22.37%	57.62%	13.84%	3.1%
MWNG_M163	30		0.00	393.33	82.92	1,789.33	21.08%	65.24%	15.16%	3.2%
NWNG_N202	28		0.00	393.33	127.33	2,838.75	32.37%	72.86%	25.78%	8.34%
NWNG_N210	30		0.00	393.33	61.00	1,339.00	15.51%	70%	11.35%	1.76%
PWNG_P110	28		0.00	393.33	198.08	4,096.33	50.36%	73.21%	37.19%	18.73%
SWNG_S034	25		0.00	393.33	213.25	3,592.00	54.22%	62.5%	36.53%	19.8%
SWNG_S035	25		0.00	393.33	207.17	4,047.17	52.67%	71.5%	41.16%	21.68%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S036	25		0.00	393.33	264.92	4,302.42	67.35%	59%	43.75%	29.47%
SWNG_S037	25		0.00	393.33	222.50	3,915.00	56.57%	71.43%	39.81%	22.52%
SWNG_S038	25		No	events found						
SWNG_S039	25		0.00	393.33	209.83	3,236.67	53.35%	67.2%	32.92%	17.56%
SWNG_S040	25		0.00	393.33	91.00	980.00	23.14%	60%	9.97%	2.31%
SWNG_S054	25		0.00	393.33	208.25	3,332.25	52.94%	50.5%	33.89%	17.94%
SWNG_S055	30		0.00	393.33	151.83	1,977.92	38.6%	40%	16.76%	6.47%
SWNG_S056	28		0.00	393.33	44.50	890.00	11.31%	71.43%	8.08%	0.91%
SWNG_S057	28		0.00	393.33	221.25	3,118.75	56.25%	41.52%	28.32%	15.93%
SWNG_S058	30		0.00	393.33	103.75	1,596.25	26.38%	41.67%	13.53%	3.57%
SWNG_S059	28		0.00	393.33	193.50	2,463.00	49.19%	45.71%	22.36%	11%
SWNG_S060	24		393.33	-0.00	1.08	26.00	0%	100%	0%	0%
SWNG_S105	77		0.00	393.33	114.75	2,768.33	29.17%	53.32%	9.14%	2.67%
SWNG_S111	30		0.00	393.33	280.08	5,192.50	71.21%	65.33%	44%	31.33%
SWNG_S113	30		0.00	393.33	190.00	3,729.17	48.31%	58.89%	31.6%	15.27%
SWNG_S125	60		0.00	393.33	156.33	3,347.50	39.75%	39.83%	14.18%	5.64%
SWNG_S220	25		0.00	393.33	170.33	2,606.50	43.31%	65.6%	26.51%	11.48%
SWNG_S221	28		0.00	393.33	220.67	3,753.33	56.1%	54.17%	34.08%	19.12%
SWNG_S224	28		0.00	393.33	221.25	4,188.75	56.25%	60.12%	38.03%	21.39%
SWNG_S225	28		0.00	393.33	184.75	2,760.50	46.97%	52.86%	25.07%	11.77%
SWNG_S226	28		0.00	393.33	161.25	3,943.75	41%	87.5%	35.81%	14.68%
SWNG_S228	28		0.00	393.33	161.00	2,721.58	40.93%	49.29%	24.71%	10.12%
SWNG_S253	30		0.00	393.33	207.50	4,080.00	52.75%	66%	34.58%	18.24%
SWNG_S258	25		0.00	393.33	192.50	3,396.25	48.94%	70%	34.54%	16.9%
SWNG_S260	28		0.00	393.33	90.00	1,605.00	22.88%	63.1%	14.57%	3.33%
SWNG_S261	20		0.00	393.33	239.92	4,399.83	61%	81.88%	55.93%	34.11%
SWNG_S263	30		0.00	393.33	180.42	2,990.42	45.87%	35.19%	25.34%	11.62%
SWNG_S264	24		0.00	393.33	194.75	3,754.25	49.51%	77.38%	39.77%	19.69%
SWNG_S266	28		0.00	393.33	192.50	2,585.00	48.94%	44.64%	23.47%	11.49%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

CapactyRatioHoursHoursUsedHoursUtilizatioUtilizatioUtilizatioUtilizatioCWNG_C113250.00393.33124.584.053.3331.67%592.67%41.22%13.06CWNG_C113250.00393.33295.005.870.0077.8355.66%70.4%80.6565.97.00CWNG_C116250.00393.33212.086.40.8353.92%44.69%65.91%35.544CWNG_C117250.00393.33190.003.620.0048.31%78.4%58.84%77.88CWNG_C113200.00393.33345.006.613.7568.35%70.6%48.40%53.24%CWNG_C132200.00393.33325.006.360.0077.8%50.66%77.8%50.66%CWNG_C132200.00393.33325.006.350.0077.8%70.8%46.67%50.66%CWNG_C133200.00393.33325.006.350.0077.8%50.66%77.8%50.66%CWNG_C134200.00393.33325.006.350.0076.9%78.8%30.66%77.8%50.66%CWNG_C134200.00393.33161.266.345.0078.8%79.8%46.67%70.66%CWNG_C13520.00393.33161.255.87.5%77.8%35.5%70.8%70.6%70.6%EWNG_E13720.00393.33161.252.67.3%64.6%20.1%10.		(A) Max	(B) Fill	(C) Blackout	(D) Possible	(E) Hours	(F) Contact	(G) Time	(H) Class Seat	(I) Station	(J) Net
CWNG_C113     25     0.00     393.33     296.00     5,870.00     75%     79.33%     59.69%     44.77       CWNG_C114     25     0.00     393.33     217.83     55.6567     70.64%     80%     55.51%     39.322       CWNG_C116     25     0.00     393.33     110.00     3.620.00     48.31%     78.4%     65.91%     43.54%       CWNG_C117     25     0.00     393.33     190.00     5.620.00     48.31%     78.4%     85.61%     17.78%       CWNG_C113     20     0.00     393.33     30.00     6.013.75     88.85%     95.62%     84.07%     17.4%     35.85%       CWNG_C132     20     0.00     393.33     325.00     6.350.00     82.63%     97.89%     80.72%     86.7       CWNG_C138     25     0.00     393.33     325.00     6.350.00     67.65%     73.81%     35.51%     20.867       EWNG_E111     30     No events found       51.5%     73.81%     35.51%     20.867											Utilization
CWN6_C114     26     0.00     393.33     277.83     5,566.67     70.64%     80%     56,51%     39.92       CWN6_C116     25     0.00     393.33     121.08     6,480.83     53.92%     469%     65,61%     39.92       CWN6_C117     25     0.00     393.33     130.00     3,62.00     48.31%     78.4%     36.81%     77.4%       CWN6_C123     25     0.00     393.33     255.00     5,366.25     64.83%     78%     64.5%     15.83       CWN6_C132     20     0.00     393.33     360.00     84.000     15.25%     70%     10.69%     16.83%       CWN6_C136     24     No events found        77.60%     80.76%     73.1%     35.51%     20.66%       EWN6_E111     30     No events found      77.64%     65.75%     73.1%     35.51%     20.66%     27.16%     11.1%     25.96%     73.51%     73.51%     35.51%     20.66%     20.60%     393.33     15.00     73.61%     73	CWNG_C110	25		0.00	393.33	124.58	4,053.33	31.67%	582.67%	41.22%	13.06%
CWNC_C116     25     0.00     393.33     212.08     6.480.83     53.92%     469%     65.91%     35.544       CWNC_C117     25     0.00     393.33     190.00     3,820.00     44.31%     77.4%     36.81%     177.74       CWNC_C112     25     0.00     393.33     247.50     6.613.75     88.35%     95.62%     84.07%     74.28       CWNC_C123     25     0.00     393.33     260.00     5.360.25     64.83%     78%     85.45%     84.07%     74.28       CWNC_C131     20     0.00     393.33     260.00     5.360.00     82.63%     97.6%     80.7%     46.53%     44.89%       CWNC_C138     25     0.00     393.33     268.25     6.345.00     67.69%     95.2%     64.53%     43.89%       EWNC_E111     30     No events found	CWNG_C113	25		0.00	393.33	295.00	5,870.00	75%	79.33%	59.69%	44.77%
CWNG_C117     25     0.00     393.33     190.00     3.820.00     48.31%     78.4%     36.81%     17.78'       CWNG_C119     20     0.00     393.33     347.50     6.613.75     68.35%     95.62%     44.07%     74.28'       CWNG_C123     25     0.00     393.33     255.00     64.83%     76%     54.57%     35.38'       CWNG_C131     20     0.00     393.33     325.00     6350.00     82.63%     97.86%     80.72%     66.7'       CWNG_C136     24     No events found         78.8%     80.72%     66.7'       EWNG_E111     30     No events found       78.8%     35.51%     20.86'       EWNG_E117     25     0.00     393.33     16.00     75.00     3.81%     20.76%     6.03'       EWNG_E119     22     0.00     393.33     16.25     2.67.37     4.1%     6.65%     2.7.1%     1.1.15'       EWNG_E126     24     0.00     393.33     1	CWNG_C114	25		0.00	393.33	277.83	5,556.67	70.64%	80%	56.51%	39.92%
CWNG_C119     20     0.00     383.33     347.50     6.613.75     88.35%     95.62%     64.07%     74.28'       CWNG_C123     25     0.00     393.33     255.00     5.366.25     64.83%     79%     54.57%     35.38'       CWNG_C132     20     0.00     393.33     325.00     840.00     15.25%     70%     10.68%     1.68''       CWNG_C132     20     0.00     393.33     325.00     65.500     76.96%     80.27%     64.53%     43.68''       CWNG_C138     25     0.00     393.33     251.08     3.352.25     58.75%     73.81%     35.51%     20.86''       EWNG_E113     24     0.00     393.33     151.00     75.00     3.81%     20%     0.76%     0.03''       EWNG_E113     24     0.00     393.33     151.00     75.00     3.81%     20%     0.76%     0.03''       EWNG_E114     24     0.00     393.33     125.20     2.82%     70.28%     64.63%     1.61''       EWNG_E131<	CWNG_C116	25		0.00	393.33	212.08	6,480.83	53.92%	469%	65.91%	35.54%
CWNG_C123     25     0.00     393.33     255.00     5,366.25     64.83%     76%     54.57%     35.38       CWNG_C131     20     0.00     393.33     60.00     840.00     15.25%     70%     10.88%     1.63'       CWNG_C132     20     0.00     393.33     326.0     6.305.00     82.65     64.83%     76%     54.57%     73.81%     1.63'       CWNG_C132     20     0.00     393.33     266.25     6.345.00     67.69%     95.2%     64.53%     73.81%     35.51%     20.60'       CWNG_C138     24     0.00     393.33     15.00     75.00     3.81%     20%     0.03'       EWNG_E113     24     0.00     393.33     116.125     2.67.375     74.1%     665'     27.1%     61.04'       EWNG_E118     25     0.00     393.33     117.50     2.532.50     2.9.87%     64.06'     20.12%     60.1'       EWNG_E137     24     0.00     393.33     117.53     2.745.75     29.46'%     66.3'%<	CWNG_C117	25		0.00	393.33	190.00	3,620.00	48.31%	78.4%	36.81%	17.78%
CWN8_C131     20     0.00     393.33     60.00     840.00     15.25%     70%     10.68%     1.83       CWN6_C132     20     0.00     393.33     325.00     6,350.00     82.63%     97.66%     80.72%     66.77       CWN6_C138     25     0.00     393.33     250.00     6,350.00     82.63%     97.66%     80.72%     66.77       CWN6_C138     25     0.00     393.33     250.25     63.50.00     82.63%     97.66%     80.72%     64.53%     36.86%       EWN6_E111     30     No events found       35.51%     73.81%     35.51%     20.86%     <	CWNG_C119	20		0.00	393.33	347.50	6,613.75	88.35%	95.62%	84.07%	74.28%
CWNG_C132     20     0.00     39.3.3     325.00     6.350.00     82.63%     97.86%     80.72%     66.77       CWNG_C136     24     No events found	CWNG_C123	25		0.00	393.33	255.00	5,366.25	64.83%	78%	54.57%	35.38%
CWNG_C136     24     No events found       CWNG_C138     25     0.00     393.33     266.25     6,345.00     67.69%     95.2%     64.53%     43.68%       EWNG_E111     30     No events found         73.81%     35.51%     20.86%       EWNG_E117     25     0.00     393.33     161.05     75.07     441%     66%     22.19%     61.01%     60.01%       EWNG_E118     25     0.00     393.33     117.50     2.532.50     29.87%     64.06%     20.12%     60.01       EWNG_E126     24     0.00     393.33     134.75     2.316.25     34.26%     72.22%     24.54%     84.41%       EWNG_E131     24     0.00     393.33     134.75     2.316.25     34.26%     72.22%     24.54%     84.41%       EWNG_E137     24     0.00     393.33     117.83     2.745.75     29.96%     96.53%     29.99%     8.71%       FWNG_F008     24     0.00     393.33     145.58     1.5	CWNG_C131	20		0.00	393.33	60.00	840.00	15.25%	70%	10.68%	1.63%
CWNG_C138     25     0.00     393.33     266.25     6,345.00     67.69%     95.2%     64.53%     43.68       EWNG_E111     30     No events found	CWNG_C132	20		0.00	393.33	325.00	6,350.00	82.63%	97.86%	80.72%	66.7%
EWNG_E111     30     No events found       EWNG_E113     24     0.00     393.33     231.08     3,352.25     58.75%     73.81%     35.51%     20.66'       EWNG_E117     25     0.00     393.33     15.00     75.00     3.81%     20%     0.06'     0.03'       EWNG_E118     25     0.00     393.33     161.25     2.673.75     41%     66%     27.19%     11.15'       EWNG_E119     32     0.00     393.33     123.29     4.275.42     59.28'     70.31%     45.29%     26.82'       EWNG_E131     24     0.00     393.33     134.75     2.316.25     34.26%     72.22%     24.54'     841'       FWNG_E137     24     0.00     393.33     117.83     2.745.75     29.96%     96.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53%     29.09%     86.53	CWNG_C136	24		No	events found						
EWNG_E113240.00393.33231.083.352.2558.75%73.81%35.51%20.86EWNG_E117250.00393.3315.0075.003.81%20%0.76%0.03EWNG_E118250.00393.33161.252,673.7541%65%27.19%11.157EWNG_E119320.00393.33117.502,532.5029.87%64.06%20.12%60.01EWNG_E126240.00393.33134.752,316.2534.26%72.22%24.54%84.41%EWNG_E131240.00393.33117.832,745.7529.96%96.53%29.09%8.71%FWNG_E137240.00393.33117.832,745.7529.96%96.53%29.09%8.71%FWNG_F005200.00393.33117.832,745.7529.96%96.53%29.09%8.71%FWNG_F011240.00393.33117.832,745.7529.96%96.53%29.09%8.71%FWNG_F015200.00393.33117.851,502.3337.01%47%19.1%7.07%FWNG_F015200.00393.33145.581,502.3337.01%47%19.1%7.07%FWNG_F113240.00393.33145.581,502.3337.01%47%19.1%7.07%FWNG_F1340No events found1778.5048.69%38.54%18.84%9.17%FWNG_F1410No event	CWNG_C138	25		0.00	393.33	266.25	6,345.00	67.69%	95.2%	64.53%	43.68%
EWNG_E117250.00393.3315.0075.003.81%20%0.76%0.033EWNG_E118250.00393.33161.252.673.7541%65%27.19%11.157EWNG_E119320.00393.33117.502,532.5029.87%64.06%20.12%66.01EWNG_E126240.00393.33134.752,316.2534.26%72.22%24.54%84.41%EWNG_E131240.00393.33117.832,745.7529.96%96.53%29.09%87.11%FWNG_F005200.00393.33117.832,745.7529.96%96.53%29.09%87.11%FWNG_F011240.00393.331103.75482.5026.88%23%6.13%1.62%FWNG_F015200.00393.331145.581,502.3337.01%47%19.1%5.89%FWNG_F113240.00393.331145.581,502.3337.01%47%19.1%5.89%FWNG_F113240.00393.33191.501,778.5048.69%38.54%18.44%9.17%FWNG_F1340No events found11.61%30.59%37.5%11.61%3.75%11.61%3.75%FWNG_F1410No events found1778.5048.69%38.54%11.61%3.75%11.67%3.75%FWNG_F1410No events found1778.5048.69%38.54%11.61%3.75%11.67%3.75% </td <td>EWNG_E111</td> <td>30</td> <td></td> <td>No</td> <td>events found</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	EWNG_E111	30		No	events found						
EWNG_E118     25     0.00     393.33     161.25     2,673.75     41%     65%     27.19%     11.15%       EWNG_E119     32     0.00     393.33     117.50     2,532.50     29.87%     64.06%     20.12%     60.01       EWNG_E126     24     0.00     393.33     232.92     4,275.42     59.22%     70.31%     45.29%     26.82%       EWNG_E131     24     0.00     393.33     134.75     2,316.25     34.26%     72.22%     24.54%     8.41%       EWNG_E137     24     0.00     393.33     103.75     482.50     26.38%     23%     6.13%     1.62%       FWNG_F005     20     0.00     393.33     103.75     482.50     26.38%     23%     6.13%     1.62%       FWNG_F013     24     0.00     393.33     145.58     1,502.33     37.01%     41%     9.17%       FWNG_F113     24     0.00     393.33     191.50     1,778.50     48.69%     38.54%     18.84%     9.17%       FWNG_F134<	EWNG_E113	24		0.00	393.33	231.08	3,352.25	58.75%	73.81%	35.51%	20.86%
EWNG_E119320.00393.33117.502,532.5029.87%64.06%20.12%6.01EWNG_E126240.00393.33232.924,275.4259.22%70.31%45.29%26.82%EWNG_E131240.00393.33134.752,316.2534.26%72.22%24.54%8.41%EWNG_E137240.00393.33117.832,745.7529.96%96.53%29.09%8.71%FWNG_F005200.00393.33103.75482.5026.38%23%6.13%1.62%FWNG_F011240.00393.33145.581,502.3337.01%39.17%15.91%5.89%FWNG_F015200.00393.33145.581,502.3337.01%47%19.1%7.07%FWNG_F113240.00393.33120.331,01.3330.59%37.5%11.67%3.57%FWNG_F1340No events found100No events found11.67%3.57%11.67%3.57%FWNG_F1410No events found100100100100100100100100100FWNG_F1420No events found10010	EWNG_E117	25		0.00	393.33	15.00	75.00	3.81%	20%	0.76%	0.03%
EWNG_E126     24     0.00     393.33     232.92     4.275.42     59.22%     70.31%     45.29%     26.82%       EWNG_E131     24     0.00     393.33     134.75     2,316.25     34.26%     72.22%     24.54%     84.41%       EWNG_E137     24     0.00     393.33     117.83     2,745.75     29.96%     96.53%     29.99%     87.44%       FWNG_F005     20     0.00     393.33     103.75     482.50     26.8%     23%     6.13%     1.62%       FWNG_F008     24     No events found	EWNG_E118	25		0.00	393.33	161.25	2,673.75	41%	65%	27.19%	11.15%
EWNG_E131     24     0.00     393.33     134.75     2,316.25     34.26%     72.22%     24.54%     8.414       EWNG_E137     24     0.00     393.33     117.83     2,745.75     29.96%     96.53%     29.09%     8.714       FWNG_F005     20     0.00     393.33     103.75     482.50     26.38%     23%     6.13%     1.624       FWNG_F008     24     No events found	EWNG_E119	32		0.00	393.33	117.50	2,532.50	29.87%	64.06%	20.12%	6.01%
EWNG_E137     24     0.00     393.33     117.83     2,745.75     29.96%     96.53%     29.09%     8.71       FWNG_F005     20     0.00     393.33     1103.75     482.50     26.38%     23%     6.13%     1.62%       FWNG_F008     24     No events found	EWNG_E126	24		0.00	393.33	232.92	4,275.42	59.22%	70.31%	45.29%	26.82%
FWNG_F005     20     0.00     393.33     103.75     482.50     26.38%     23%     6.13%     1.62%       FWNG_F008     24     No events found	EWNG_E131	24		0.00	393.33	134.75	2,316.25	34.26%	72.22%	24.54%	8.41%
FWNG_F008     24     No events found       FWNG_F011     24     0.00     393.33     145.58     1,502.33     37.01%     39.17%     15.91%     5.89%       FWNG_F015     20     0.00     393.33     145.58     1,502.33     37.01%     47%     19.1%     7.07%       FWNG_F015     20     0.00     393.33     191.50     1,778.50     48.69%     38.54%     18.84%     9.17%       FWNG_F113     24     0.00     393.33     120.33     1,101.33     30.59%     37.5%     11.67%     35.7%       FWNG_F134     0     No events found     No events found     V	EWNG_E137	24		0.00	393.33	117.83	2,745.75	29.96%	96.53%	29.09%	8.71%
FWNG_F011   24   0.00   393.33   145.58   1,502.33   37.01%   39.17%   15.91%   5.89     FWNG_F015   20   0.00   393.33   145.58   1,502.33   37.01%   47%   19.1%   7.074     FWNG_F111   24   0.00   393.33   191.50   1,778.50   48.69%   38.54%   18.84%   9.174     FWNG_F113   24   0.00   393.33   120.33   1,101.33   30.59%   37.5%   11.67%   35.74     FWNG_F134   0   No events found   Vertex found	FWNG_F005	20		0.00	393.33	103.75	482.50	26.38%	23%	6.13%	1.62%
FWNG_F015     20     0.00     393.33     145.58     1,502.33     37.01%     47%     19.1%     7.07%       FWNG_F111     24     0.00     393.33     191.50     1,778.50     48.69%     38.54%     18.84%     9.17%       FWNG_F113     24     0.00     393.33     120.33     1,101.33     30.59%     37.5%     11.67%     3.57%       FWNG_F134     0     No events found     Vertities found	FWNG_F008	24		No	events found						
FWNG_F111     24     0.00     393.33     191.50     1,778.50     48.69%     38.54%     18.84%     9.17       FWNG_F113     24     0.00     393.33     120.33     1,101.33     30.59%     37.5%     11.67%     3.574       FWNG_F134     0     No events found     V	FWNG_F011	24		0.00	393.33	145.58	1,502.33	37.01%	39.17%	15.91%	5.89%
FWNG_F113     24     0.00     393.33     120.33     1,101.33     30.59%     37.5%     11.67%     3.57%       FWNG_F134     0     No events found     V     <	FWNG_F015	20		0.00	393.33	145.58	1,502.33	37.01%	47%	19.1%	7.07%
FWNG_F134   0   No events found     FWNG_F140   0   No events found     FWNG_F141   0   No events found     FWNG_F142   0   No events found	FWNG_F111	24		0.00	393.33	191.50	1,778.50	48.69%	38.54%	18.84%	9.17%
FWNG_F1400No events foundFWNG_F1410No events foundFWNG_F1420No events found	FWNG_F113	24		0.00	393.33	120.33	1,101.33	30.59%	37.5%	11.67%	3.57%
FWNG_F141 0 No events found   FWNG_F142 0 No events found	FWNG_F134	0		No	events found						
FWNG_F142 0 No events found	FWNG_F140	0		No	events found						
	FWNG_F141	0		No	events found						
FWNG_F143 0 No events found	FWNG_F142	0		No	events found						
	FWNG_F143	0		No	events found						

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
FWNG_F144	Capacity 0	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F145	0			events found						
FWNG_F146	0			events found						
FWNG_F150	50		0.00	393.33	285.50	4,905.00	72.58%	28.6%	24.94%	18.1%
FWNG_F158	20		0.00	393.33	134.42	2,209.08	34.17%	80.71%	28.08%	9.6%
FWNG_F268	23		0.00	393.33	239.75	3,567.75	60.95%	61.74%	37.79%	23.04%
FWNG_F277	10			events found	200.10	0,007.10	00.0070	01.1470	01.1070	20.0470
FWNG_F279	10			events found						
FWNG_F283A	0		0.00	393.33	25.33	621.17	6.44%	0%	0%	0%
FWNG_F283B	0		0.00	393.33	43.42	1,164.83	11.04%	0%	0%	0%
FWNG_F283C	0		0.00	393.33	49.08	1,175.00	12.48%	0%	0%	0%
FWNG_F283D	0		0.00	393.33	12.25	277.67	3.11%	0%	0%	0%
FWNG_F284	20		0.00	393.33	90.08	1,318.00	22.9%	108.75%	16.75%	3.84%
FWNG_F286	0		0.00	393.33	36.92	815.83	9.39%	0%	0%	0%
FWNG_F287	0		0.00	393.33	9.92	283.83	2.52%	0%	0%	0%
FWNG_F288	20		0.00	393.33	60.50	1,187.50	15.38%	96.43%	15.1%	2.32%
FWNG_F289	20		0.00	393.33	86.58	1,997.33	22.01%	109.23%	25.39%	5.59%
FWNG_F290	20		0.00	393.33	81.42	1,888.50	20.7%	111.25%	24.01%	4.97%
FWNG_F291	20		0.00	393.33	76.42	1,055.67	19.43%	102.86%	13.42%	2.61%
GWNG_G162	30	0		events found		,				
GWNG_G164	25			events found						
LWNG_L118	22		0.00	393.33	56.92	560.42	14.47%	36.36%	6.48%	0.94%
LWNG_L125	20		0.00	393.33	210.42	1,690.42	53.5%	28.12%	21.49%	11.5%
LWNG_L126	25		0.00	393.33	19.67	196.67	5%	40%	2%	0.1%
LWNG_L126A	25		0.00	393.33	19.67	196.67	5%	40%	2%	0.1%
LWNG_L126B	25		0.00	393.33	4.92	49.17	1.25%	40%	0.5%	0.01%
 LWNG_L130	34		0.00	393.33	54.00	669.83	13.73%	35.29%	5.01%	0.69%
_ LWNG_L140	20		0.00	393.33	283.33	2,651.50	72.03%	47%	33.71%	24.28%
MWNG_M110	20		0.00	393.33	221.00	2,575.67	56.19%	43%	32.74%	18.4%
MWNG_M115	20			events found						
	20		0.00	393.33	15.00	210.00	3.81%	70%	2.67%	0.1%
MWNG_M140	20		0.00	393.33	15.00	210.00	3.81%	70%	2.67%	0.

Report Date: Oct 14 2019 11:55 A.M.

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
MWNG_M145	20		0.00	393.33	15.00	123.75	3.81%	22.5%	1.57%	0.06%
MWNG_M150	24		0.00	393.33	81.75	8,578.00	20.78%	1600%	90.87%	18.89%
MWNG_M150A	20		No	o events found						
MWNG_M150B	20		No	o events found						
MWNG_M150C	20		No	o events found						
MWNG_M150D	20		No	o events found						
MWNG_M153	30		0.00	393.33	221.00	2,575.67	56.19%	28.67%	21.83%	12.26%
MWNG_M156	20		0.00	393.33	37.50	337.50	9.53%	45%	4.29%	0.41%
MWNG_M161	30		No	o events found						
MWNG_M162	30		0.00	393.33	54.58	1,665.83	13.88%	231.67%	14.12%	1.96%
NWNG_N200	24		0.00	393.33	30.00	510.00	7.63%	70.83%	5.4%	0.41%
NWNG_N204	18		0.00	393.33	12.92	206.67	3.28%	88.89%	2.92%	0.1%
NWNG_N206	26		0.00	393.33	96.00	936.00	24.41%	51.92%	9.15%	2.23%
NWNG_N208	24		0.00	393.33	171.75	2,815.00	43.67%	48.15%	29.82%	13.02%
PWNG_P120	30		0.00	393.33	60.42	1,089.17	15.36%	65%	9.23%	1.42%
PWNG_P121	30		0.00	393.33	15.42	369.17	3.92%	76.67%	3.13%	0.12%
PWNG_P126	30		No	o events found						
PWNG_P150	30		0.00	393.33	33.58	671.67	8.54%	66.67%	5.69%	0.49%
PWNG_P209	30		0.00	393.33	78.75	1,435.00	20.02%	67.22%	12.16%	2.43%
PWNG_P211	30		0.00	393.33	151.58	2,276.92	38.54%	50.33%	19.3%	7.44%
SIML	0		No	o events found						
SWNG_S041	24		0.00	393.33	103.75	1,072.50	26.38%	43.75%	11.36%	3%
SWNG_S104	25		0.00	393.33	175.00	3,417.50	44.49%	77%	34.75%	15.46%
SWNG_S130	16		0.00	393.33	30.00	210.00	7.63%	43.75%	3.34%	0.25%
SWNG_S131	60		No	o events found						
SWNG_S134	25		0.00	393.33	90.00	900.00	22.88%	40%	9.15%	2.09%
SWNG_S139	20		0.00	393.33	90.00	1,350.00	22.88%	75%	17.16%	3.93%
SWNG_S140	20		0.00	393.33	27.50	165.00	6.99%	30%	2.1%	0.15%
SWNG_S201	25		0.00	393.33	117.50	1,610.00	29.87%	58%	16.37%	4.89%
SWNG_S204	25		0.00	393.33	235.00	4,470.00	59.75%	76%	45.46%	27.16%
SWNG_S232	20		No	o events found						

Report Date: Oct 14 2019 11:55 A.M.

# Location Utilization Summary

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S234	20		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A120	18		No	events found						
AWNG_A121	22		0.00	153.33	15.00	240.00	9.78%	72.73%	7.11%	0.7%
AWNG_A122	22		No	events found						
AWNG_A123	20		0.00	153.33	19.42	77.83	12.66%	57.5%	2.54%	0.32%
AWNG_A124	20		0.00	153.33	10.25	26.75	6.68%	32.5%	0.87%	0.06%
AWNG_A125	22		0.00	153.33	37.33	622.58	24.35%	67.42%	18.46%	4.49%
AWNG_A135	28		No	events found						
JWNG_J130	20		0.00	153.33	13.08	173.42	8.53%	45.71%	5.65%	0.48%
KWNG_K104	21		0.00	153.33	44.67	774.00	29.13%	82.54%	24.04%	7%
KWNG_K105	18		0.00	153.33	30.00	450.00	19.57%	83.33%	16.3%	3.19%
KWNG_K107	19		0.00	153.33	15.00	270.00	9.78%	94.74%	9.27%	0.91%
KWNG_K109	23		0.00	153.33	31.50	539.00	20.54%	60.87%	15.28%	3.14%
KWNG_K110	16		0.00	153.33	6.50	130.00	4.24%	125%	5.3%	0.22%
KWNG_K111	24		0.00	153.33	3.50	80.50	2.28%	95.83%	2.19%	0.05%
KWNG_K114	20		0.00	153.33	49.08	876.33	32.01%	88.57%	28.58%	9.15%
LWNG_L105	21		0.00	153.33	15.92	222.17	10.38%	21.43%	6.9%	0.72%
MWNG_M100	20		0.00	153.33	41.42	741.08	27.01%	71.11%	24.17%	6.53%
MWNG_M103	20		0.00	153.33	34.17	549.42	22.28%	66.25%	17.92%	3.99%
SWNG_S101	21		0.00	153.33	58.58	1,229.17	38.21%	97.62%	38.17%	14.58%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A035	24		7.67	145.67	20.92	196.75	14.36%	62.08%	5.63%	0.81%
AWNG_A203	30		0.00	153.33	85.00	1,797.50	55.43%	71.11%	39.08%	21.66%
AWNG_A204	30		0.00	153.33	86.25	1,897.50	56.25%	73.33%	41.25%	23.2%
AWNG_A205	36		0.00	153.33	57.50	890.00	37.5%	43.06%	16.12%	6.05%
AWNG_A206	30		0.00	153.33	57.50	1,305.00	37.5%	75%	28.37%	10.64%
AWNG_A207	36		0.00	153.33	30.00	480.00	19.57%	44.44%	8.7%	1.7%
AWNG_A208	30		0.00	153.33	65.17	1,423.33	42.5%	71.11%	30.94%	13.15%
AWNG_A209	36		0.00	153.33	87.50	1,722.50	57.07%	55.56%	31.2%	17.81%
AWNG_A211	24		0.00	153.33	58.58	1,056.67	38.21%	79.17%	28.71%	10.97%
AWNG_A213	30		0.00	153.33	57.50	1,207.50	37.5%	70%	26.25%	9.84%
CWNG_C111	58		0.00	153.33	141.83	13,527.83	92.5%	35.96%	152.11%	140.7%
DWNG_D133	40		0.00	153.33	59.42	1,265.83	38.75%	75.83%	20.64%	8%
DWNG_D135	40		0.00	153.33	58.75	1,410.00	38.32%	60%	22.99%	8.81%
EWNG_E110	38		0.00	153.33	48.00	1,223.67	31.3%	81.58%	21%	6.57%
EWNG_E112	38		0.00	153.33	22.83	530.83	14.89%	82.89%	9.11%	1.36%
EWNG_E114	32		0.00	153.33	15.92	367.00	10.38%	73.44%	7.48%	0.78%
EWNG_E116	32		0.00	153.33	86.00	2,172.92	56.09%	60.94%	44.28%	24.84%
FWNG_F012	32		0.00	153.33	61.92	767.25	40.38%	25%	15.64%	6.31%
FWNG_F020	24		0.00	153.33	10.17	192.50	6.63%	72.92%	5.23%	0.35%
FWNG_F023	32		0.00	153.33	17.83	760.00	11.63%	304.69%	15.49%	1.8%
FWNG_F024	32		0.00	153.33	5.92	340.00	3.86%	281.25%	6.93%	0.27%
FWNG_F025	50		0.00	153.33	21.58	1,064.83	14.08%	130.67%	13.89%	1.96%
FWNG_F026	32		0.00	153.33	17.75	496.25	11.58%	266.41%	10.11%	1.17%
FWNG_F027	32		0.00	153.33	13.83	560.17	9.02%	241.25%	11.42%	1.03%
FWNG_F028	32		0.00	153.33	2.42	281.67	1.58%	500%	5.74%	0.09%
FWNG_F029	32		0.00	153.33	20.08	315.33	13.1%	63.28%	6.43%	0.84%
FWNG_F031	32		0.00	153.33	8.83	212.00	5.76%	75%	4.32%	0.25%
FWNG_F032	32		0.00	153.33	21.92	637.75	14.29%	91.52%	13%	1.86%
FWNG_F033	32		0.00	153.33	34.50	933.00	22.5%	75%	19.01%	4.28%
FWNG_F034	32		0.00	153.33	7.67	111.17	5%	45.31%	2.27%	0.11%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F035	24		0.00	153.33	15.00	270.00	9.78%	75%	7.34%	0.72%
FWNG_F036	30		0.00	153.33	15.00	270.00	9.78%	60%	5.87%	0.57%
FWNG_F120	32		0.00	153.33	69.67	1,240.83	45.43%	58.48%	25.29%	11.49%
FWNG_F130	24		0.00	153.33	35.83	540.58	23.37%	58.33%	14.69%	3.43%
FWNG_F264	32		0.00	153.33	15.92	300.00	10.38%	69.06%	6.11%	0.63%
FWNG_F282	20		No	o events found						
GWNG_G163	25		0.00	153.33	24.92	338.08	16.25%	64%	8.82%	1.43%
JWNG_J132	32		0.00	153.33	43.17	990.25	28.15%	71.88%	20.18%	5.68%
JWNG_J133	32		0.00	153.33	93.75	2,018.75	61.14%	66.41%	41.14%	25.16%
JWNG_J134	32		0.00	153.33	43.75	676.25	28.53%	46.88%	13.78%	3.93%
JWNG_J135	32		0.00	153.33	84.08	2,679.25	54.84%	74.22%	54.6%	29.94%
JWNG_J136	32		0.00	153.33	59.42	989.00	38.75%	68.75%	20.16%	7.81%
JWNG_J137	32		0.00	153.33	45.00	585.00	29.35%	42.19%	11.92%	3.5%
JWNG_J138	32		0.00	153.33	51.25	807.50	33.42%	50%	16.46%	5.5%
JWNG_J139	32		0.00	153.33	102.50	1,980.00	66.85%	60.94%	40.35%	26.98%
JWNG_J140	32		0.00	153.33	28.75	718.75	18.75%	78.12%	14.65%	2.75%
JWNG_J141	32		0.00	153.33	15.00	375.00	9.78%	78.12%	7.64%	0.75%
KWNG_K116	26		0.00	153.33	30.00	660.00	19.57%	84.62%	16.56%	3.24%
LWNG_L112	24		0.00	153.33	42.50	255.00	27.72%	25%	6.93%	1.92%
LWNG_L114	24		0.00	153.33	13.75	178.75	8.97%	27.08%	4.86%	0.44%
LWNG_L131	34		0.00	153.33	13.75	178.75	8.97%	19.12%	3.43%	0.31%
LWNG_L141	20		0.00	153.33	55.67	556.67	36.3%	50%	18.15%	6.59%
MWNG_M104	30		0.00	153.33	15.92	326.58	10.38%	81.67%	7.1%	0.74%
MWNG_M105	24		0.00	153.33	143.75	7,513.33	93.75%	105.56%	204.17%	191.41%
MWNG_M151	30		0.00	153.33	4.25	58.33	2.77%	41.67%	1.27%	0.04%
MWNG_M163	30		0.00	153.33	35.17	936.17	22.93%	58.89%	20.35%	4.67%
NWNG_N202	28		0.00	153.33	10.50	210.00	6.85%	71.43%	4.89%	0.33%
NWNG_N210	30		0.00	153.33	13.75	165.00	8.97%	40%	3.59%	0.32%
PWNG_P110	28		0.00	153.33	17.58	302.58	11.47%	75.89%	7.05%	0.81%
SWNG_S034	25		0.00	153.33	53.92	1,057.50	35.16%	88%	27.59%	9.7%
SWNG_S035	25		0.00	153.33	88.17	1,813.17	57.5%	64%	47.3%	27.2%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S036	25		0.00	153.33	44.42	581.92	28.97%	44%	15.18%	4.4%
SWNG_S037	25		0.00	153.33	73.75	885.00	48.1%	48%	23.09%	11.1%
SWNG_S038	25		No	events found						
SWNG_S039	25		0.00	153.33	57.67	578.33	37.61%	60%	15.09%	5.67%
SWNG_S040	25		0.00	153.33	1.92	47.92	1.25%	100%	1.25%	0.02%
SWNG_S054	25		0.00	153.33	16.92	271.92	11.03%	38%	7.09%	0.78%
SWNG_S055	30		0.00	153.33	15.00	210.00	9.78%	25%	4.57%	0.45%
SWNG_S056	28		0.00	153.33	0.92	27.50	0.6%	107.14%	0.64%	0%
SWNG_S057	28		0.00	153.33	60.00	670.00	39.13%	33.04%	15.61%	6.11%
SWNG_S058	30		No	events found						
SWNG_S059	28		No	events found						
SWNG_S060	24		No	events found						
SWNG_S105	77		0.00	153.33	17.00	661.67	11.09%	43.02%	5.6%	0.62%
SWNG_S111	30		0.00	153.33	43.75	581.25	28.53%	43.33%	12.64%	3.61%
SWNG_S113	30		0.00	153.33	5.00	100.00	3.26%	66.67%	2.17%	0.07%
SWNG_S125	60		0.00	153.33	68.33	1,607.50	44.57%	48.61%	17.47%	7.79%
SWNG_S220	25		0.00	153.33	8.17	203.00	5.33%	96%	5.3%	0.28%
SWNG_S221	28		0.00	153.33	19.17	38.33	12.5%	7.14%	0.89%	0.11%
SWNG_S224	28		0.00	153.33	87.17	976.25	56.85%	56.25%	22.74%	12.93%
SWNG_S225	28		0.00	153.33	15.00	210.00	9.78%	50%	4.89%	0.48%
SWNG_S226	28		0.00	153.33	45.00	1,095.00	29.35%	85.71%	25.5%	7.49%
SWNG_S228	28		0.00	153.33	15.00	285.00	9.78%	67.86%	6.64%	0.65%
SWNG_S253	30		0.00	153.33	15.00	360.00	9.78%	80%	7.83%	0.77%
SWNG_S258	25		0.00	153.33	43.75	616.25	28.53%	62%	16.08%	4.59%
SWNG_S260	28		No	events found						
SWNG_S261	20		0.00	153.33	57.58	888.83	37.55%	74%	28.98%	10.88%
SWNG_S263	30		No	events found						
SWNG_S264	24		0.00	153.33	42.50	382.50	27.72%	37.5%	10.39%	2.88%
SWNG_S266	28		0.00	153.33	15.00	240.00	9.78%	57.14%	5.59%	0.55%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
CWNG_C110	25		No	events found						
CWNG_C113	25		0.00	153.33	115.00	2,300.00	75%	80%	60%	45%
CWNG_C114	25		0.00	153.33	80.67	1,613.33	52.61%	80%	42.09%	22.14%
CWNG_C116	25		0.00	153.33	57.50	1,437.50	37.5%	100%	37.5%	14.06%
CWNG_C117	25		0.00	153.33	115.00	2,300.00	75%	80%	60%	45%
CWNG_C119	20		0.00	153.33	115.00	2,271.25	75%	98.33%	74.06%	55.55%
CWNG_C123	25		0.00	153.33	28.75	201.25	18.75%	28%	5.25%	0.98%
CWNG_C131	20		No	events found						
CWNG_C132	20		0.00	153.33	115.00	2,300.00	75%	100%	75%	56.25%
CWNG_C136	24		No	events found						
CWNG_C138	25		0.00	153.33	58.75	1,410.00	38.32%	96%	36.78%	14.09%
EWNG_E111	30		No	events found						
EWNG_E113	24		0.00	153.33	78.83	1,727.00	51.41%	87.5%	46.93%	24.13%
EWNG_E117	25		No	events found						
EWNG_E118	25		0.00	153.33	45.00	855.00	29.35%	76%	22.3%	6.55%
EWNG_E119	32		0.00	153.33	15.00	375.00	9.78%	78.12%	7.64%	0.75%
EWNG_E126	24		0.00	153.33	45.67	833.17	29.78%	54.17%	22.64%	6.74%
EWNG_E131	24		0.00	153.33	7.50	172.50	4.89%	95.83%	4.69%	0.23%
EWNG_E137	24		0.00	153.33	71.25	1,681.25	46.47%	98.61%	45.69%	21.23%
FWNG_F005	20		0.00	153.33	22.50	90.00	14.67%	20%	2.93%	0.43%
FWNG_F008	24		No	events found						
FWNG_F011	24		0.00	153.33	31.25	297.50	20.38%	29.17%	8.08%	1.65%
FWNG_F015	20		0.00	153.33	31.25	297.50	20.38%	35%	9.7%	1.98%
FWNG_F111	24		0.00	153.33	43.00	346.00	28.04%	35.42%	9.4%	2.64%
FWNG_F113	24		0.00	153.33	26.75	267.50	17.45%	41.67%	7.27%	1.27%
FWNG_F134	0		No	events found						
FWNG_F140	0		No	events found						
FWNG_F141	0		No	events found						
FWNG_F142	0		No	events found						
FWNG_F143	0		No	events found						

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max Capacity	Fill Ratio	Blackout Hours	Possible Hours	Hours Used	Contact Hours	Time Utilization	Class Seat Utilization	Station Utilization	Net Utilization
FWNG_F144	0	Rutio		events found	0000	nouro	otilization	Othization	Otimzation	othization
 FWNG_F145	0		No	events found						
 FWNG_F146	0		No	events found						
FWNG_F150	50		0.00	153.33	101.00	1,591.75	65.87%	27.33%	20.76%	13.68%
FWNG_F158	20		0.00	153.33	57.25	908.00	37.34%	85%	29.61%	11.05%
FWNG_F268	24		0.00	153.33	15.00	195.00	9.78%	54.17%	5.3%	0.52%
FWNG_F277	10		No	events found						
FWNG_F279	10		No	events found						
FWNG_F283A	0		0.00	153.33	0.08	2.50	0.05%	0%	0%	0%
FWNG_F283B	0		0.00	153.33	3.50	93.00	2.28%	0%	0%	0%
FWNG_F283C	0		0.00	153.33	3.42	87.33	2.23%	0%	0%	0%
FWNG_F283D	0		No	events found						
FWNG_F284	20		0.00	153.33	1.25	15.83	0.82%	100%	0.52%	0%
FWNG_F286	0		0.00	153.33	0.42	10.33	0.27%	0%	0%	0%
FWNG_F287	0		0.00	153.33	0.17	4.50	0.11%	0%	0%	0%
FWNG_F288	20		0.00	153.33	1.33	32.50	0.87%	127.5%	1.06%	0.01%
FWNG_F289	20		0.00	153.33	15.75	287.33	10.27%	112%	9.37%	0.96%
FWNG_F290	20		0.00	153.33	15.75	287.33	10.27%	112%	9.37%	0.96%
FWNG_F291	20		0.00	153.33	4.08	69.67	2.66%	96%	2.27%	0.06%
GWNG_G162	30	0	No	events found						
GWNG_G164	25		No	events found						
LWNG_L118	22		0.00	153.33	7.58	75.83	4.95%	45.45%	2.25%	0.11%
LWNG_L125	20		0.00	153.33	41.25	288.75	26.9%	35%	9.42%	2.53%
LWNG_L126	25		0.00	153.33	3.33	33.33	2.17%	40%	0.87%	0.02%
LWNG_L126A	25		0.00	153.33	3.33	33.33	2.17%	40%	0.87%	0.02%
LWNG_L126B	25		0.00	153.33	0.08	0.83	0.05%	40%	0.02%	0%
LWNG_L130	34		No	events found						
LWNG_L140	20		0.00	153.33	55.67	524.33	36.3%	46.67%	17.1%	6.21%
MWNG_M110	20		0.00	153.33	107.33	1,821.17	70%	62.86%	59.39%	41.57%
MWNG_M115	20		No	events found						
MWNG_M140	20		0.00	153.33	28.75	258.75	18.75%	45%	8.44%	1.58%

Report Date: Oct 14 2019 12:07 P.M.

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
MWNG_M145	20			events found						
MWNG_M150	24		0.00	153.33	15.08	305.00	9.84%	3150%	8.29%	0.82%
MWNG_M150A	20			events found						
MWNG_M150B	20			events found						
MWNG_M150C	20			events found						
MWNG_M150D	20			events found						
MWNG_M153	30		0.00	153.33	106.17	1,807.17	69.24%	41.9%	39.29%	27.2%
MWNG_M156	20		No	events found						
MWNG_M161	30		No	events found						
MWNG_M162	30		0.00	153.33	4.42	304.17	2.88%	300%	6.61%	0.19%
NWNG_N200	24		0.00	153.33	13.75	275.00	8.97%	83.33%	7.47%	0.67%
NWNG_N204	18		No	events found						
NWNG_N206	26		No	events found						
NWNG_N208	24		No	events found						
PWNG_P120	30		0.00	153.33	0.50	11.00	0.33%	73.33%	0.24%	0%
PWNG_P121	30		0.00	153.33	0.50	11.00	0.33%	73.33%	0.24%	0%
PWNG_P126	30		No	events found						
PWNG_P150	30		No	events found						
PWNG_P209	30		0.00	153.33	58.58	1,284.42	38.21%	70%	27.92%	10.67%
PWNG_P211	30		0.00	153.33	13.25	303.83	8.64%	90%	6.61%	0.57%
SIML	0		No	events found						
SWNG_S041	24		0.00	153.33	28.75	690.00	18.75%	100%	18.75%	3.52%
SWNG_S104	25		0.00	153.33	87.50	1,660.00	57.07%	74%	43.3%	24.71%
SWNG_S130	16		No	events found						
SWNG_S131	60		No	events found						
SWNG_S134	25		No	events found						
SWNG_S139	20		No	events found						
SWNG_S140	20		0.00	153.33	57.50	345.00	37.5%	30%	11.25%	4.22%
SWNG_S201	25		0.00	153.33	57.50	920.00	37.5%	64%	24%	9%
SWNG_S204	25		0.00	153.33	87.50	1,630.00	57.07%	72%	42.52%	24.27%
SWNG_S232	20		No	events found						

Report Date: Oct 14 2019 12:07 P.M.

# Location Utilization Summary

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S234	20		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A120	18		No events found							
AWNG_A121	22		1.92	391.42	135.00	1,890.00	34.49%	63.64%	21.95%	7.57%
AWNG_A122	22		1.92	391.42	45.00	675.00	11.5%	68.18%	7.84%	0.9%
AWNG_A123	20		1.92	391.42	77.58	881.17	19.82%	79.38%	11.26%	2.23%
AWNG_A124	20		1.92	391.42	94.67	1,252.00	24.19%	68%	15.99%	3.87%
AWNG_A125	22		1.92	391.42	138.17	1,927.92	35.3%	60%	22.39%	7.9%
AWNG_A135	28		No	events found						
JWNG_J130	20		1.92	391.42	2.25	45.00	0.57%	100%	0.57%	0%
KWNG_K104	21		1.92	391.42	166.67	1,953.17	42.58%	65.87%	23.76%	10.12%
KWNG_K105	18		1.92	391.42	241.50	2,916.00	61.7%	68.89%	41.39%	25.54%
KWNG_K107	19		1.92	391.42	141.00	2,538.00	36.02%	94.74%	34.13%	12.29%
KWNG_K109	23		1.92	391.42	99.08	1,628.25	25.31%	69.57%	18.09%	4.58%
KWNG_K110	16		1.92	391.42	58.75	738.75	15.01%	78.12%	11.8%	1.77%
KWNG_K111	24		1.92	391.42	95.25	1,324.42	24.33%	80.56%	14.1%	3.43%
KWNG_K114	20		1.92	391.42	105.67	1,228.00	27%	72%	15.69%	4.23%
LWNG_L105	21		1.92	391.42	177.42	1,815.42	45.33%	18.45%	22.09%	10.01%
MWNG_M100	20		1.92	391.42	67.92	880.83	17.35%	50%	11.25%	1.95%
MWNG_M103	20		1.92	391.42	135.00	2,155.00	34.49%	58.33%	27.53%	9.49%
SWNG_S101	21		1.92	391.42	62.50	1,312.50	15.97%	100%	15.97%	2.55%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A035	24		21.58	371.75	33.83	154.50	9.1%	36.67%	1.73%	0.16%
AWNG_A203	30		1.92	391.42	180.00	3,750.00	45.99%	72.5%	31.94%	14.69%
AWNG_A204	30		1.92	391.42	165.00	3,930.00	42.15%	78.89%	33.47%	14.11%
AWNG_A205	36		1.92	391.42	178.75	5,193.75	45.67%	58.33%	36.86%	16.83%
AWNG_A206	30		1.92	391.42	165.00	2,925.00	42.15%	57.78%	24.91%	10.5%
AWNG_A207	36		1.92	391.42	118.75	2,542.50	30.34%	59.72%	18.04%	5.47%
AWNG_A208	30		1.92	391.42	151.33	2,714.67	38.66%	56%	23.12%	8.94%
AWNG_A209	36		1.92	391.42	91.08	1,714.33	23.27%	38.89%	12.17%	2.83%
AWNG_A211	24		No	events found						
AWNG_A213	30		1.92	391.42	150.00	1,260.00	38.32%	28.89%	10.73%	4.11%
CWNG_C111	58		1.92	391.42	0.08	4.17	0.02%	86.21%	0.02%	0%
DWNG_D133	40		1.92	391.42	180.08	4,324.17	46.01%	81.67%	27.62%	12.71%
DWNG_D135	40		1.92	391.42	157.50	3,465.00	40.24%	55%	22.13%	8.91%
EWNG_E110	38		1.92	391.42	66.67	402.00	17.03%	47.37%	2.7%	0.46%
EWNG_E112	38		No	events found						
EWNG_E114	32		1.92	391.42	102.17	1,155.58	26.1%	54.69%	9.23%	2.41%
EWNG_E116	32		1.92	391.42	158.08	3,953.67	40.39%	60.16%	31.57%	12.75%
FWNG_F012	32		1.92	391.42	30.00	420.00	7.66%	43.75%	3.35%	0.26%
FWNG_F020	24		No	events found						
FWNG_F023	32		1.92	391.42	84.83	2,035.00	21.67%	67.19%	16.25%	3.52%
FWNG_F024	32		1.92	391.42	12.58	314.17	3.21%	70.31%	2.51%	0.08%
FWNG_F025	50		1.92	391.42	3.00	85.17	0.77%	66.5%	0.44%	0%
FWNG_F026	32		1.92	391.42	45.00	576.25	11.5%	26.04%	4.6%	0.53%
FWNG_F027	32		1.92	391.42	46.67	1,385.42	11.92%	85.94%	11.06%	1.32%
FWNG_F028	32		No	events found						
FWNG_F029	32		1.92	391.42	15.00	210.00	3.83%	43.75%	1.68%	0.06%
FWNG_F031	32		1.92	391.42	5.92	142.00	1.51%	75%	1.13%	0.02%
FWNG_F032	32		1.92	391.42	0.58	16.92	0.15%	90.62%	0.14%	0%
FWNG_F033	32		1.92	391.42	78.00	1,023.00	19.93%	44.79%	8.17%	1.63%
FWNG_F034	32		1.92	391.42	8.67	247.58	2.21%	73.12%	1.98%	0.04%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F035	24		1.92	391.42	95.42	1,761.67	24.38%	63.54%	18.75%	4.57%
FWNG_F036	30		1.92	391.42	45.00	360.00	11.5%	26.67%	3.07%	0.35%
FWNG_F120	32		1.92	391.42	16.42	330.58	4.19%	63.12%	2.64%	0.11%
FWNG_F130	24		1.92	391.42	37.50	712.50	9.58%	76.39%	7.58%	0.73%
FWNG_F264	32		1.92	391.42	161.42	3,180.50	41.24%	46.35%	25.39%	10.47%
FWNG_F282	20		No	o events found						
GWNG_G163	25		1.92	391.42	62.00	1,121.00	15.84%	61.33%	11.46%	1.81%
JWNG_J132	32		1.92	391.42	103.08	2,016.83	26.34%	68.75%	16.1%	4.24%
JWNG_J133	32		1.92	391.42	148.75	2,556.25	38%	53.12%	20.41%	7.76%
JWNG_J134	32		1.92	391.42	197.50	4,371.25	50.46%	69.53%	34.9%	17.61%
JWNG_J135	32		1.92	391.42	209.00	3,666.00	53.4%	56.25%	29.27%	15.63%
JWNG_J136	32		1.92	391.42	157.58	2,538.00	40.26%	67.19%	20.26%	8.16%
JWNG_J137	32		1.92	391.42	146.75	1,861.50	37.49%	39.58%	14.86%	5.57%
JWNG_J138	32		1.92	391.42	150.00	2,475.00	38.32%	51.56%	19.76%	7.57%
JWNG_J139	32		1.92	391.42	193.75	4,327.50	49.5%	71.09%	34.55%	17.1%
JWNG_J140	32		1.92	391.42	195.00	2,850.00	49.82%	50%	22.75%	11.34%
JWNG_J141	32		1.92	391.42	135.00	1,395.00	34.49%	32.29%	11.14%	3.84%
KWNG_K116	26		1.92	391.42	75.00	645.00	19.16%	34.62%	6.34%	1.21%
LWNG_L112	24		1.92	391.42	122.50	1,807.50	31.3%	35.71%	19.24%	6.02%
LWNG_L114	24		1.92	391.42	77.08	954.58	19.69%	32.74%	10.16%	2%
LWNG_L131	34		1.92	391.42	134.92	1,805.42	34.47%	36.47%	13.57%	4.68%
LWNG_L141	20		1.92	391.42	242.67	2,305.33	62%	47.5%	29.45%	18.26%
MWNG_M104	30		1.92	391.42	208.08	1,261.92	53.16%	39.17%	10.75%	5.71%
MWNG_M105	24		1.92	391.42	222.50	1,393.75	56.84%	26.39%	14.84%	8.43%
MWNG_M151	30		1.92	391.42	180.42	1,252.42	46.09%	24.17%	10.67%	4.92%
MWNG_M163	30		1.92	391.42	82.50	952.50	21.08%	22.67%	8.11%	1.71%
NWNG_N202	28		1.92	391.42	119.33	1,742.75	30.49%	42.14%	15.9%	4.85%
NWNG_N210	30		1.92	391.42	134.50	2,038.25	34.36%	41.33%	17.36%	5.96%
PWNG_P110	28		1.92	391.42	134.83	2,817.08	34.45%	75.89%	25.7%	8.85%
SWNG_S034	25		1.92	391.42	109.08	1,772.50	27.87%	80%	18.11%	5.05%
SWNG_S035	25		1.92	391.42	75.08	900.08	19.18%	33.33%	9.2%	1.76%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S036	25		1.92	391.42	30.08	240.08	7.69%	18%	2.45%	0.19%
SWNG_S037	25		1.92	391.42	193.75	3,568.75	49.5%	70.4%	36.47%	18.05%
SWNG_S038	25		No	events found						
SWNG_S039	25		1.92	391.42	120.00	2,262.50	30.66%	50.67%	23.12%	7.09%
SWNG_S040	25		1.92	391.42	60.00	720.00	15.33%	48%	7.36%	1.13%
SWNG_S054	25		1.92	391.42	45.08	585.08	11.52%	28%	5.98%	0.69%
SWNG_S055	30		1.92	391.42	2.92	72.92	0.75%	83.33%	0.62%	0%
SWNG_S056	28		1.92	391.42	4.08	122.50	1.04%	107.14%	1.12%	0.01%
SWNG_S057	28		No	events found						
SWNG_S058	30		No	events found						
SWNG_S059	28		No	events found						
SWNG_S060	24		No	events found						
SWNG_S105	77		1.92	391.42	90.67	1,148.33	23.16%	30.84%	3.81%	0.88%
SWNG_S111	30		1.92	391.42	195.00	2,865.00	49.82%	50.83%	24.4%	12.16%
SWNG_S113	30		1.92	391.42	90.00	1,665.00	22.99%	61.67%	14.18%	3.26%
SWNG_S125	60		1.92	391.42	52.50	947.50	13.41%	38.75%	4.03%	0.54%
SWNG_S220	25		1.92	391.42	47.50	847.50	12.14%	66%	8.66%	1.05%
SWNG_S221	28		No	events found						
SWNG_S224	28		1.92	391.42	19.08	272.50	4.88%	71.43%	2.49%	0.12%
SWNG_S225	28		No	events found						
SWNG_S226	28		No	events found						
SWNG_S228	28		No	events found						
SWNG_S253	30		No	events found						
SWNG_S258	25		No	events found						
SWNG_S260	28		No	events found						
SWNG_S261	20		1.92	391.42	169.17	3,047.67	43.22%	87%	38.93%	16.83%
SWNG_S263	30		1.92	391.42	3.00	60.00	0.77%	66.67%	0.51%	0%
SWNG_S264	24		1.92	391.42	163.75	1,832.50	41.84%	45.83%	19.51%	8.16%
SWNG_S266	28		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
CWNG_C110	25		1.92	391.42	60.00	780.00	15.33%	52%	7.97%	1.22%
CWNG_C113	25		1.92	391.42	180.00	3,600.00	45.99%	80%	36.79%	16.92%
CWNG_C114	25		1.92	391.42	207.50	4,150.00	53.01%	80%	42.41%	22.48%
CWNG_C116	25		1.92	391.42	145.75	2,151.25	37.24%	54%	21.98%	8.19%
CWNG_C117	25		1.92	391.42	195.00	2,910.00	49.82%	65.33%	29.74%	14.82%
CWNG_C119	20		1.92	391.42	150.00	2,992.50	38.32%	98.75%	38.23%	14.65%
CWNG_C123	25		1.92	391.42	135.00	2,205.00	34.49%	58%	22.53%	7.77%
CWNG_C131	20		No	events found						
CWNG_C132	20		1.92	391.42	180.00	3,510.00	45.99%	97.5%	44.84%	20.62%
CWNG_C136	24		No	events found						
CWNG_C138	25		1.92	391.42	135.08	1,936.67	34.51%	66.67%	19.79%	6.83%
EWNG_E111	30		No	events found						
EWNG_E113	24		1.92	391.42	113.17	1,726.00	28.91%	75%	18.37%	5.31%
EWNG_E117	25		1.92	391.42	64.17	1,292.58	16.39%	84%	13.21%	2.17%
EWNG_E118	25		1.92	391.42	195.00	2,207.50	49.82%	30.67%	22.56%	11.24%
EWNG_E119	32		1.92	391.42	135.00	1,845.00	34.49%	51.56%	14.73%	5.08%
EWNG_E126	24		1.92	391.42	162.58	1,722.58	41.54%	36.46%	18.34%	7.62%
EWNG_E131	24		1.92	391.42	157.50	3,202.50	40.24%	77.08%	34.09%	13.72%
EWNG_E137	24		1.92	391.42	202.50	4,642.50	51.74%	95.83%	49.42%	25.57%
FWNG_F005	20		No	events found						
FWNG_F008	24		No	events found						
FWNG_F011	24		1.92	391.42	2.08	31.25	0.53%	62.5%	0.33%	0%
FWNG_F015	20		1.92	391.42	2.08	31.25	0.53%	75%	0.4%	0%
FWNG_F111	24		No	events found						
FWNG_F113	24		1.92	391.42	7.50	75.00	1.92%	41.67%	0.8%	0.02%
FWNG_F134	0		No	events found						
FWNG_F140	0		No	events found						
FWNG_F141	0		No	events found						
FWNG_F142	0		No	events found						
FWNG_F143	0		No	events found						

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F144	0			events found						
FWNG_F145	0			events found						
FWNG_F146	0			events found						
FWNG_F150	50			o events found						
FWNG_F158	20		1.92	391.42	15.00	300.00	3.83%	100%	3.83%	0.15%
FWNG_F268	24			o events found						
FWNG_F277	10		No	o events found						
FWNG_F279	10		No	events found						
FWNG_F283A	0		No	events found						
FWNG_F283B	0		1.92	391.42	1.08	30.33	0.28%	0%	0%	0%
FWNG_F283C	0		No	o events found						
FWNG_F283D	0		No	o events found						
FWNG_F284	20		No	o events found						
FWNG_F286	0		No	o events found						
FWNG_F287	0		No	o events found						
FWNG_F288	20		1.92	391.42	110.25	1,764.00	28.17%	80%	22.53%	6.35%
FWNG_F289	20		1.92	391.42	61.92	463.67	15.82%	83.75%	5.92%	0.94%
FWNG_F290	20		1.92	391.42	1.92	43.67	0.49%	100%	0.56%	0%
FWNG_F291	20		1.92	391.42	0.58	9.33	0.15%	80%	0.12%	0%
GWNG_G162	30	0	No	o events found						
GWNG_G164	25		No	o events found						
LWNG_L118	22		1.92	391.42	88.75	1,106.25	22.67%	29.55%	12.85%	2.91%
LWNG_L125	20		1.92	391.42	275.00	3,381.25	70.26%	25.91%	43.19%	30.35%
LWNG_L126	25		1.92	391.42	60.00	830.00	15.33%	28%	8.48%	1.3%
LWNG_L126A	25		No	o events found						
LWNG_L126B	25		No	o events found						
LWNG_L130	34		1.92	391.42	60.00	660.00	15.33%	32.35%	4.96%	0.76%
LWNG_L140	20		1.92	391.42	242.67	2,305.33	62%	47.5%	29.45%	18.26%
MWNG_M110	20		1.92	391.42	313.50	5,349.08	80.09%	39.29%	68.33%	54.73%
 MWNG_M115	20		1.92	391.42	235.00	4,136.67	60.04%	41.92%	52.84%	31.73%
 MWNG_M140	20		1.92	391.42	195.00	3,245.00	49.82%	56.43%	41.45%	20.65%

Report Date: Oct 14 2019 12:10 P.M.

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
MWNG_M145	20		1.92	391.42	90.00	1,006.25	22.99%	28.75%	12.85%	2.96%
MWNG_M150	24		1.92	391.42	45.00	218.75	11.5%	10.42%	2.33%	0.27%
MWNG_M150A	20			o events found						
MWNG_M150B	20		1.92	391.42	45.00	450.00	11.5%	50%	5.75%	0.66%
MWNG_M150C	20		No	o events found						
MWNG_M150D	20		No	o events found						
MWNG_M153	30		1.92	391.42	229.83	1,921.50	58.72%	29.05%	16.36%	9.61%
MWNG_M156	20		No	o events found						
MWNG_M161	30		1.92	391.42	231.25	2,657.50	59.08%	38%	22.63%	13.37%
MWNG_M162	30		1.92	391.42	81.25	1,187.50	20.76%	25.24%	10.11%	2.1%
NWNG_N200	24		1.92	391.42	15.00	300.00	3.83%	83.33%	3.19%	0.12%
NWNG_N204	18		1.92	391.42	90.00	1,327.50	22.99%	41.67%	18.84%	4.33%
NWNG_N206	26		1.92	391.42	237.50	2,152.50	60.68%	17.95%	21.15%	12.83%
NWNG_N208	24		1.92	391.42	237.50	2,921.25	60.68%	26.04%	31.1%	18.87%
PWNG_P120	30		No	o events found						
PWNG_P121	30		No	o events found						
PWNG_P126	30		No	o events found						
PWNG_P150	30		1.92	391.42	49.08	1,472.50	12.54%	100%	12.54%	1.57%
PWNG_P209	30		1.92	391.42	133.75	2,355.00	34.17%	63.81%	20.06%	6.85%
PWNG_P211	30		1.92	391.42	60.08	513.33	15.35%	63.33%	4.37%	0.67%
SIML	0		No	o events found						
SWNG_S041	24		No	o events found						
SWNG_S104	25		1.92	391.42	60.00	1,020.00	15.33%	68%	10.42%	1.6%
SWNG_S130	16		No	o events found						
SWNG_S131	60		1.92	391.42	90.00	2,963.75	22.99%	14.17%	12.62%	2.9%
SWNG_S134	25		No	o events found						
SWNG_S139	20		1.92	391.42	90.00	900.00	22.99%	50%	11.5%	2.64%
SWNG_S140	20		No	o events found						
SWNG_S201	25		1.92	391.42	90.00	720.00	22.99%	32%	7.36%	1.69%
SWNG_S204	25		No	o events found						
SWNG_S232	20		No	o events found						

Report Date: Oct 14 2019 12:10 P.M.

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S234	20		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A120	18		No	events found						
AWNG_A121	22		No	events found						
AWNG_A122	22		No	events found						
AWNG_A123	20		No	events found						
AWNG_A124	20		No	events found						
AWNG_A125	22		No	events found						
AWNG_A135	28		No	events found						
JWNG_J130	20		No	events found						
KWNG_K104	21		No	events found						
KWNG_K105	18		No	events found						
KWNG_K107	19		No	events found						
KWNG_K109	23		No	events found						
KWNG_K110	16		No	events found						
KWNG_K111	24		No	events found						
KWNG_K114	20		21.83	349.33	4.08	77.58	1.17%	95%	1.11%	0.01%
LWNG_L105	21		21.83	349.33	21.25	212.50	6.08%	47.62%	2.9%	0.18%
MWNG_M100	20		21.83	349.33	4.08	81.67	1.17%	100%	1.17%	0.01%
MWNG_M103	20		No	events found						
SWNG_S101	21		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	<b>(I)</b>	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
AWNG_A035	24		21.83	349.33	19.00	140.25	5.44%	35.42%	1.67%	0.09%
AWNG_A203	30		No	events found						
AWNG_A204	30		No	events found						
AWNG_A205	36		No	events found						
AWNG_A206	30		No	events found						
AWNG_A207	36		No	events found						
AWNG_A208	30		No	events found						
AWNG_A209	36		No	events found						
AWNG_A211	24		No	events found						
AWNG_A213	30		No	events found						
CWNG_C111	58		21.83	349.33	6.58	6,583.33	1.88%	1724.14%	32.49%	0.61%
DWNG_D133	40		No	events found						
DWNG_D135	40		No	events found						
EWNG_E110	38		21.83	349.33	6.58	6,583.33	1.88%	2631.58%	49.59%	0.93%
EWNG_E112	38		21.83	349.33	6.58	6,583.33	1.88%	2631.58%	49.59%	0.93%
EWNG_E114	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
EWNG_E116	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F012	32		21.83	349.33	37.50	367.50	10.73%	29.17%	3.29%	0.35%
FWNG_F020	24		21.83	349.33	6.58	6,583.33	1.88%	4166.67%	78.52%	1.48%
FWNG_F023	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F024	32		21.83	349.33	10.75	6,687.50	3.08%	1601.56%	59.82%	1.84%
FWNG_F025	50		21.83	349.33	6.58	6,583.33	1.88%	2000%	37.69%	0.71%
FWNG_F026	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F027	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F028	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F029	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
FWNG_F031	32		21.83	349.33	11.17	7,408.33	3.2%	1843.75%	66.27%	2.12%
FWNG_F032	32		21.83	349.33	11.17	7,408.33	3.2%	1843.75%	66.27%	2.12%
FWNG_F033	32		21.83	349.33	11.17	7,408.33	3.2%	1843.75%	66.27%	2.12%
FWNG_F034	32		21.83	349.33	11.17	7,408.33	3.2%	1843.75%	66.27%	2.12%

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
FWNG_F035	24		21.83	349.33	11.17	7,408.33	3.2%	2458.33%	88.36%	2.82%
FWNG_F036	30		21.83	349.33	11.17	7,408.33	3.2%	1966.67%	70.69%	2.26%
FWNG_F120	32		No	events found						
FWNG_F130	24		21.83	349.33	4.08	61.25	1.17%	62.5%	0.73%	0.01%
FWNG_F264	32		No	events found						
FWNG_F282	20		21.83	349.33	120.00	720.00	34.35%	30%	10.31%	3.54%
GWNG_G163	25		No	events found						
JWNG_J132	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J133	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J134	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J135	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J136	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J137	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J138	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J139	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J140	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
JWNG_J141	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
KWNG_K116	26		No	events found						
LWNG_L112	24		21.83	349.33	8.08	161.67	2.31%	83.33%	1.93%	0.04%
LWNG_L114	24		No	events found						
LWNG_L131	34		No	events found						
LWNG_L141	20		No	events found						
MWNG_M104	30		21.83	349.33	28.58	571.67	8.18%	66.67%	5.45%	0.45%
MWNG_M105	24		21.83	349.33	16.33	326.67	4.68%	83.33%	3.9%	0.18%
MWNG_M151	30		21.83	349.33	6.58	6,583.33	1.88%	3333.33%	62.82%	1.18%
MWNG_M163	30		21.83	349.33	6.58	6,583.33	1.88%	3333.33%	62.82%	1.18%
NWNG_N202	28		No	events found						
NWNG_N210	30		No	events found						
PWNG_P110	28		21.83	349.33	6.58	6,583.33	1.88%	3571.43%	67.31%	1.27%
SWNG_S034	25		No	events found						
SWNG_S035	25		No	events found						

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S036	25		No	o events found						
SWNG_S037	25		No	o events found						
SWNG_S038	25		No	o events found						
SWNG_S039	25		No	o events found						
SWNG_S040	25		No	o events found						
SWNG_S054	25		No	o events found						
SWNG_S055	30		No	o events found						
SWNG_S056	28		No	o events found						
SWNG_S057	28		No	o events found						
SWNG_S058	30		No	o events found						
SWNG_S059	28		No	o events found						
SWNG_S060	24		No	o events found						
SWNG_S105	77		No	o events found						
SWNG_S111	30		No	o events found						
SWNG_S113	30		No	o events found						
SWNG_S125	60		No	o events found						
SWNG_S220	25		No	o events found						
SWNG_S221	28		No	o events found						
SWNG_S224	28		No	o events found						
SWNG_S225	28		No	o events found						
SWNG_S226	28		21.83	349.33	45.00	1,125.00	12.88%	89.29%	11.5%	1.48%
SWNG_S228	28		No	o events found						
SWNG_S253	30		No	o events found						
SWNG_S258	25		No	o events found						
SWNG_S260	28		No	o events found						
SWNG_S261	20		No	o events found						
SWNG_S263	30		No	o events found						
SWNG_S264	24		No	o events found						
SWNG_S266	28		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
CWNG_C110	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
CWNG_C113	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
CWNG_C114	25		No	o events found						
CWNG_C116	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
CWNG_C117	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
CWNG_C119	20		No	o events found						
CWNG_C123	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
CWNG_C131	20		No	o events found						
CWNG_C132	20		No	o events found						
CWNG_C136	24		21.83	349.33	6.58	6,583.33	1.88%	4166.67%	78.52%	1.48%
CWNG_C138	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
EWNG_E111	30		No	o events found						
EWNG_E113	24		21.83	349.33	6.58	6,583.33	1.88%	4166.67%	78.52%	1.48%
EWNG_E117	25		No	o events found						
EWNG_E118	25		21.83	349.33	6.58	6,583.33	1.88%	4000%	75.38%	1.42%
EWNG_E119	32		21.83	349.33	6.58	6,583.33	1.88%	3125%	58.89%	1.11%
EWNG_E126	24		21.83	349.33	6.58	6,583.33	1.88%	4166.67%	78.52%	1.48%
EWNG_E131	24		No	o events found						
EWNG_E137	24		No	o events found						
FWNG_F005	20		No	o events found						
FWNG_F008	24		No	o events found						
FWNG_F011	24		No	o events found						
FWNG_F015	20		No	o events found						
FWNG_F111	24		No	o events found						
FWNG_F113	24		No	o events found						
FWNG_F134	0		No	o events found						
FWNG_F140	0		No	o events found						
FWNG_F141	0		No	o events found						
FWNG_F142	0		No	o events found						
FWNG_F143	0		No	o events found						

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max Capacity	Fill Ratio	Blackout Hours	Possible Hours	Hours Used	Contact Hours	Time Utilization	Class Seat Utilization	Station Utilization	Net Utilization
FWNG_F144	0			o events found						
FWNG_F145	0		No	o events found						
FWNG_F146	0		No	o events found						
FWNG_F150	50		No	o events found						
FWNG_F158	20		No	o events found						
FWNG_F268	24		No	o events found						
FWNG_F277	10		No	o events found						
FWNG_F279	10		No	o events found						
FWNG_F283A	0		No	o events found						
FWNG_F283B	0		No	o events found						
FWNG_F283C	0		No	o events found						
FWNG_F283D	0		No	o events found						
FWNG_F284	20		21.83	349.33	42.50	425.00	12.17%	50%	6.08%	0.74%
FWNG_F286	0		No	o events found						
FWNG_F287	0		No	o events found						
FWNG_F288	20		No	o events found						
FWNG_F289	20		No	o events found						
FWNG_F290	20		No	o events found						
FWNG_F291	20		21.83	349.33	36.50	365.00	10.45%	50%	5.22%	0.55%
GWNG_G162	30	0	21.83	349.33	16.00	400.00	4.58%	83.33%	3.82%	0.17%
GWNG_G164	25		No	o events found						
LWNG_L118	22		No	o events found						
LWNG_L125	20		21.83	349.33	21.25	212.50	6.08%	50%	3.04%	0.19%
LWNG_L126	25		No	o events found						
LWNG_L126A	25		No	o events found						
LWNG_L126B	25		No	o events found						
LWNG_L130	34		No	o events found						
LWNG_L140	20		No	o events found						
MWNG_M110	20		No	o events found						
MWNG_M115	20		No	o events found						
MWNG_M140	20		No	o events found						

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
MWNG_M145	20		21.83	349.33	6.58	6,583.33	1.88%	5000%	94.23%	1.78%
MWNG_M150	24			events found						
MWNG_M150A	20			o events found						
MWNG_M150B	20			o events found						
MWNG_M150C	20			o events found						
MWNG_M150D	20			events found						
MWNG_M153	30		21.83	349.33	6.58	6,583.33	1.88%	3333.33%	62.82%	1.18%
MWNG_M156	20		No	events found						
MWNG_M161	30		21.83	349.33	6.58	6,583.33	1.88%	3333.33%	62.82%	1.18%
MWNG_M162	30		No	o events found						
NWNG_N200	24		No	o events found						
NWNG_N204	18		No	o events found						
NWNG_N206	26		No	o events found						
NWNG_N208	24		No	o events found						
PWNG_P120	30		No	events found						
PWNG_P121	30		No	events found						
PWNG_P126	30		No	o events found						
PWNG_P150	30		21.83	349.33	25.25	3,748.33	7.23%	1716.67%	35.77%	2.59%
PWNG_P209	30		No	o events found						
PWNG_P211	30		No	o events found						
SIML	0		No	o events found						
SWNG_S041	24		No	o events found						
SWNG_S104	25		No	o events found						
SWNG_S130	16		No	o events found						
SWNG_S131	60		No	o events found						
SWNG_S134	25		No	o events found						
SWNG_S139	20		No	events found						
SWNG_S140	20		No	o events found						
SWNG_S201	25		No	events found						
	25		No	o events found						
	20		No	o events found						

Report Date: Oct 14 2019 11:46 A.M.

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SWNG_S234	20		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_117	25		0.00	153.33	11.83	236.67	7.72%	80%	6.17%	0.48%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_212	30		No	events found						
BAY_213	30		0.00	153.33	45.00	630.00	29.35%	46.67%	13.7%	4.02%
BAY_215	30		No	events found						
BAY_217	26		0.00	153.33	42.50	510.00	27.72%	46.15%	12.79%	3.55%
BAY_221	24		0.00	153.33	71.25	1,408.75	46.47%	79.17%	38.28%	17.79%
BAY_223	24		0.00	153.33	45.00	540.00	29.35%	50%	14.67%	4.31%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

#### Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

#### Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

#### Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

#### Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

#### Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_117	25		0.00	393.33	8.03	160.67	2.04%	80%	1.63%	0.03%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_212	30		0.00	393.33	23.83	190.67	6.06%	26.67%	1.62%	0.1%
BAY_213	30		0.00	393.33	10.50	199.50	2.67%	63.33%	1.69%	0.05%
BAY_215	30		No	events found						
BAY_217	26		0.00	393.33	106.25	2,116.25	27.01%	70.51%	20.69%	5.59%
BAY_221	24		0.00	393.33	58.75	936.25	14.94%	68.06%	9.92%	1.48%
BAY_223	24		0.00	393.33	27.50	302.50	6.99%	45.83%	3.2%	0.22%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_117	25		0.00	153.33	0.92	18.33	0.6%	80%	0.48%	0%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_212	30		0.00	153.33	26.00	208.00	16.96%	26.67%	4.52%	0.77%
BAY_213	30		No	events found						
BAY_215	30		No	events found						
BAY_217	26		0.00	153.33	13.75	275.00	8.97%	76.92%	6.9%	0.62%
BAY_221	24		0.00	153.33	57.50	1,092.50	37.5%	79.17%	29.69%	11.13%
BAY_223	24		0.00	153.33	57.50	632.50	37.5%	45.83%	17.19%	6.45%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_117	25		1.92	391.42	1.08	21.67	0.28%	80%	0.22%	0%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_212	30		No	events found						
BAY_213	30		1.92	391.42	50.17	1,069.00	12.82%	75%	9.1%	1.17%
BAY_215	30		No	events found						
BAY_217	26		1.92	391.42	142.00	2,008.00	36.28%	58.97%	19.73%	7.16%
BAY_221	24		No	events found						
BAY_223	24		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

## Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_117	25		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
BAY_212	30		No	events found						
BAY_213	30		No	events found						
BAY_215	30		No	events found						
BAY_217	26		No	events found						
BAY_221	24		No	events found						
BAY_223	24		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_201	19		0.00	153.33	49.67	836.17	32.39%	92.98%	28.7%	9.3%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_103	32		0.00	153.33	55.00	1,031.25	35.87%	55.21%	21.02%	7.54%
DCMC_104	32		0.00	153.33	27.50	440.00	17.93%	50%	8.97%	1.61%
DCMC_105	32		No	events found						
DCMC_106	32		No	events found						
DCMC_153	30		0.00	153.33	27.50	550.00	17.93%	66.67%	11.96%	2.14%
DCMC_154	30		0.00	153.33	26.25	322.50	17.12%	40%	7.01%	1.2%
DCMC_155	30		0.00	153.33	57.50	1,380.00	37.5%	80%	30%	11.25%
DCMC_156	30		0.00	153.33	85.00	1,475.00	55.43%	57.78%	32.07%	17.78%
DCMC_203	32		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_202	20		No	events found						
DCMC_204	24		0.00	153.33	28.75	431.25	18.75%	31.25%	11.72%	2.2%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_201	19		0.00	393.33	226.83	4,150.67	57.67%	95.61%	55.54%	32.03%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_103	32		0.00	393.33	90.00	1,590.00	22.88%	55.21%	12.63%	2.89%
DCMC_104	32		0.00	393.33	90.00	900.00	22.88%	35.94%	7.15%	1.64%
DCMC_105	32		No	events found						
DCMC_106	32		No	events found						
DCMC_153	30		0.00	393.33	147.50	2,950.00	37.5%	66.67%	25%	9.37%
DCMC_154	30		0.00	393.33	105.00	1,440.00	26.69%	44.44%	12.2%	3.26%
DCMC_155	30		0.00	393.33	208.75	3,246.25	53.07%	52.78%	27.51%	14.6%
DCMC_156	30		0.00	393.33	60.00	1,020.00	15.25%	56.67%	8.64%	1.32%
DCMC_203	32		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_202	20		No	events found						
DCMC_204	24		0.00	393.33	73.75	1,106.25	18.75%	31.25%	11.72%	2.2%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_201	19		0.00	153.33	63.58	1,173.75	41.47%	93.42%	40.29%	16.71%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_103	32		No	events found						
DCMC_104	32		No	events found						
DCMC_105	32		Nc	events found						
DCMC_106	32		No	events found						
DCMC_153	30		0.00	153.33	30.00	600.00	19.57%	66.67%	13.04%	2.55%
DCMC_154	30		0.00	153.33	27.50	467.50	17.93%	56.67%	10.16%	1.82%
DCMC_155	30		0.00	153.33	28.75	546.25	18.75%	63.33%	11.88%	2.23%
DCMC_156	30		No	events found						
DCMC_203	32		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_202	20		No	events found						
DCMC_204	24		0.00	153.33	23.75	346.25	15.49%	31.25%	9.41%	1.46%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_201	19		1.92	391.42	109.75	893.58	28.04%	67.37%	12.02%	3.37%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_103	32		1.92	391.42	60.00	1,080.00	15.33%	56.25%	8.62%	1.32%
DCMC_104	32		No	events found						
DCMC_105	32		No	events found						
DCMC_106	32		1.92	391.42	52.50	682.50	13.41%	40.62%	5.45%	0.73%
DCMC_153	30		1.92	391.42	90.00	1,800.00	22.99%	66.67%	15.33%	3.52%
DCMC_154	30		1.92	391.42	135.00	1,980.00	34.49%	55.56%	16.86%	5.82%
DCMC_155	30		1.92	391.42	105.00	1,185.00	26.83%	40%	10.09%	2.71%
DCMC_156	30		1.92	391.42	135.00	1,350.00	34.49%	31.67%	11.5%	3.97%
DCMC_203	32		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_202	20		No	events found						
DCMC_204	24		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_201	19		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

## Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

## Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_103	32		No	events found						_
DCMC_104	32		No	events found						
DCMC_105	32		No	events found						
DCMC_106	32		No	events found						
DCMC_153	30		No	events found						
DCMC_154	30		No	events found						
DCMC_155	30		No	events found						
DCMC_156	30		No	events found						
DCMC_203	32		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
DCMC_202	20		No	events found						
DCMC_204	24		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

## Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_200	25		0.00	153.33	41.50	355.83	27.07%	37.33%	9.28%	2.51%
SAG_210	25		0.00	153.33	62.92	1,132.50	41.03%	72%	29.54%	12.12%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

## Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

## Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

## Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

## Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

## Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_230	30		0.00	153.33	29.42	633.75	19.18%	61.67%	13.78%	2.64%
SAG_232	25		0.00	153.33	3.83	3.83	2.5%	4%	0.1%	0%
SAG_302	30		0.00	153.33	78.58	1,048.42	51.25%	48.33%	22.79%	11.68%
SAG_304	30		0.00	153.33	12.50	212.50	8.15%	56.67%	4.62%	0.38%
SAG_305	40		No	events found						
SAG_306	30		0.00	153.33	76.58	703.17	49.95%	40%	15.29%	7.63%
SAG_308	30		0.00	153.33	85.00	1,480.00	55.43%	57.78%	32.17%	17.84%
SAG_310	30		0.00	153.33	147.58	4,427.50	96.25%	100%	96.25%	92.64%
SAG_311	20		0.00	153.33	72.50	1,395.00	47.28%	95%	45.49%	21.51%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 8:00 A.M. to 9:55 A.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_120	24		0.00	153.33	1.92	34.50	1.25%	75%	0.94%	0.01%
SAG_205	25		0.00	153.33	85.00	1,700.00	55.43%	80%	44.35%	24.58%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_200	25		0.00	393.33	164.25	1,615.92	41.76%	56%	16.43%	6.86%
SAG_210	25		0.00	393.33	170.75	3,180.83	43.41%	86%	32.35%	14.04%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_230	30		0.00	393.33	136.17	2,753.75	34.62%	64.17%	23.34%	8.08%
SAG_232	25		0.00	393.33	13.75	17.67	3.5%	6%	0.18%	0.01%
SAG_302	30		0.00	393.33	213.67	3,286.17	54.32%	45.24%	27.85%	15.13%
SAG_304	30		0.00	393.33	195.33	2,410.00	49.66%	42.08%	20.42%	10.14%
SAG_305	40		0.00	393.33	7.67	153.33	1.95%	50%	0.97%	0.02%
SAG_306	30		0.00	393.33	183.00	2,523.50	46.53%	47.22%	21.39%	9.95%
SAG_308	30		0.00	393.33	155.25	2,730.00	39.47%	51.43%	23.14%	9.13%
SAG_310	30		0.00	393.33	378.58	11,357.50	96.25%	100%	96.25%	92.64%
SAG_311	20		0.00	393.33	30.00	540.00	7.63%	90%	6.86%	0.52%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

# Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 10:00 A.M. to 2:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_120	24		0.00	393.33	9.75	190.83	2.48%	79.17%	2.02%	0.05%
SAG_205	25		0.00	393.33	295.00	3,902.50	75%	63%	39.69%	29.76%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

# Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_200	25		0.00	153.33	6.75	147.75	4.4%	68%	3.85%	0.17%
SAG_210	25		0.00	153.33	28.75	372.25	18.75%	72%	9.71%	1.82%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_230	30		0.00	153.33	58.58	1,281.25	38.21%	61.67%	27.85%	10.64%
SAG_232	25		0.00	153.33	34.00	247.58	22.17%	50.67%	6.46%	1.43%
SAG_302	30		0.00	153.33	41.75	454.50	27.23%	30%	9.88%	2.69%
SAG_304	30		0.00	153.33	72.50	1,225.00	47.28%	51.11%	26.63%	12.59%
SAG_305	40		0.00	153.33	4.33	86.67	2.83%	50%	1.41%	0.04%
SAG_306	30		0.00	153.33	87.58	1,102.08	57.12%	52.22%	23.96%	13.68%
SAG_308	30		0.00	153.33	58.75	918.75	38.32%	51.67%	19.97%	7.65%
SAG_310	30		0.00	153.33	147.58	4,427.50	96.25%	100%	96.25%	92.64%
SAG_311	20		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 3:00 P.M. to 4:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 153.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_120	24		0.00	153.33	4.33	86.67	2.83%	83.33%	2.36%	0.07%
SAG_205	25		0.00	153.33	115.00	2,415.00	75%	84%	63%	47.25%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_200	25		1.92	391.42	47.25	724.17	12.07%	65%	7.4%	0.89%
SAG_210	25		1.92	391.42	63.00	468.00	16.1%	34%	4.78%	0.77%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Мах	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_230	30		1.92	391.42	147.00	2,880.00	37.56%	66.67%	24.53%	9.21%
SAG_232	25		1.92	391.42	9.58	122.00	2.45%	74.67%	1.25%	0.03%
SAG_302	30		1.92	391.42	47.08	551.67	12.03%	48.89%	4.7%	0.57%
SAG_304	30		1.92	391.42	78.00	1,230.00	19.93%	48.89%	10.47%	2.09%
SAG_305	40		1.92	391.42	120.00	1,650.00	30.66%	31.67%	10.54%	3.23%
SAG_306	30		1.92	391.42	178.92	2,507.92	45.71%	56.67%	21.36%	9.76%
SAG_308	30		1.92	391.42	90.00	1,485.00	22.99%	55%	12.65%	2.91%
SAG_310	30		1.92	391.42	160.42	4,812.50	40.98%	100%	40.98%	16.8%
SAG_311	20		No	events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 5:00 P.M. to 9:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 393.33 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_120	24		1.92	391.42	177.00	3,360.00	45.22%	77.5%	35.77%	16.17%
SAG_205	25		1.92	391.42	135.00	2,610.00	34.49%	82%	26.67%	9.2%

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

#### Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_200	25		No	o events found						
SAG_210	25		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

#### Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_230	30		No	o events found						
SAG_232	25		No	events found						
SAG_302	30		No	events found						
SAG_304	30		No	o events found						
SAG_305	40		No	events found						
SAG_306	30		No	o events found						
SAG_308	30		No	o events found						
SAG_310	30		No	o events found						
SAG_311	20		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

#### Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K

Based on events from 8:00 A.M. to 6:55 P.M., between Aug 24 2019 and Dec 15 2019. There are 371.17 total hours in the report period, (K).

	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)	(I)	(J)
	Max	Fill	Blackout	Possible	Hours	Contact	Time	Class Seat	Station	Net
	Capacity	Ratio	Hours	Hours	Used	Hours	Utilization	Utilization	Utilization	Utilization
SAG_120	24		No events found							
SAG_205	25		No	o events found						

Maximum Capacity and Fill Ratio are values that may be provided for a location. The location utilization computations cannot be made where Maximum Capacity has not been specified.

# Column C

Blackout Hours is the total hours of all blackout dates defined for a location for this report time period.

# Column D

Possible Hours is calculated by taking the total possible hours for the report period (K) defined by the user report parameters and subtracting the total blackout hours for the location during that same time period.

# Column E

Hours Used is the total number of hours for all occurrences assigned to this location during the report period.

# Column F

Contact Hours is the product of (column I), Total Hours Used, and the Selected Head Count for each reservation in the report period.

# Column G

Time Utilization is the percentage of hours a location is used during the report period. This is the quotient of (column E), Hours Used, divided by (column D), Possible Hours. This value is expressed as a percentage.

# Column H

Class Seat Utilization is the average percentage of seats used for each reservation compared to the Maximum Capacity of the location. Class Seat Utilization is calculated by taking the Selected Head Count, divided by (column A), Maximum Capacity, multiplied by 100. This value is expressed as a percentage.

# Column I

Station Utilization is the percentage of total contact hours compared to the total possible contact hours for the location during the report period. The total possible contact hours is the (column A), Maximum Capacity, multiplied by (column D), Total Possible Hours. This value is expressed as a percentage.

# Column J

Net Utilization is the product of (column G), Time Utilization, and (column I), Station Utilization. This value is expressed as a percentage.

# Column K